



POPULAR USES OF POWER CARRIERS

- Hire companies
- Vineyards
- Construction sites
- Stone masons
- Emergency services
- Railways
- Landscape gardening
- Agricultural applications
- Forestry work
- Mining work
- Mountain path repairs
- Humanitarian aid
- Recovery work
- Landscape/beach restoration

OUR RANGE OF POWER CARRIERS

Safe and easy to operate, Honda Power Carriers are true savers of time and labour. Robust, durable and driven by a 4-stroke engine with smooth power and high torque, they take the backache out of shifting heavy loads, especially in limited access areas. The ideal accomplice to an endless variety of jobs, you will wonder how you ever managed before owning one.

LOW GROUND PRESSURE MAXIMUM FLEXIBILITY

Our HP range of tracked power carriers is perfect for moving large loads in restricted spaces, over soft ground or on undulating terrain. The unique track tread pattern provides incredible traction, even up steps, but minimises ground damage which is particularly useful over lawns and gardens. Each track is independently controlled by the left and right hand levers, for easy manoeuvrability and a 71cm turning radius.

All models feature a deadman's clutch that disengages the drive when you let go, ensuring controllability and safety. The narrow width means access through a standard doorway is no problem and allows impressive manoeuvrability where space is limited.

The HP 500 model also features a hydrostatic drive system, for smoother forward and reverse operation.



HP 500

KEY FEATURES AND TECHNOLOGY

- HYDRO**
HYDROSTATIC DRIVE
Variable speed drive for smooth control and improved comfort.
- UNIQUE TRACK PATTERN**
Superb stability and traction for low ground-pressure and minimal surface damage.
- DMC**
DEADMAN'S CLUTCH
Releasing the special handles stops the carrier for added safety and control.
- INDEPENDENT TRACK CONTROL**
Left and right tracks are controlled by separate levers for a small turning radius.
- ADJUSTABLE LOAD BED**
Expandable carrying bed for extra large loads.
- TILTING LOAD BED**
Fully tilting load bed allows for easy unloading.



Max load (level ground)	500kg
Max load (sloping ground)	350kg
Max load height – level ground	900mm
Max forward speed	4.3km/h
Max reverse speed	3.6km/h
Max upward gradient	25°
Max downward gradient	25°
Engine model	GX160
Net power (SAE J1349)	3.6kW / 3,600rpm
Fuel tank capacity	3.1L
Dry weight	197kg
Overall dimensions (mm)	L 2140 × W 650 × H 1100
Bed dimensions (mm)	L 1200 × W 560 × H 200
Sound power level (2000/14/EC, 2005/88/EC)	99dB(A)

*The HP 500 is available with or without the adjustable load bed.