



## Stainless Steel Valves



### Tech Sheet 10216

#### Manifold Valves

2 Valve manifold pipe to pipe design for separate mounting, connection system impulse lines and transmitters, having a simple 2 valve configuration, which allows for easy block, bleed and calibration of static pressure transmitter of gauge.

Other mounting options are available on request.



2 Valve Manifold, Pipe to Pipe, NPT

0380 £  
P2VM-SS-8-R 1/2" 89.30

2 Valve manifold remote mount flange to flange design for separate mounting, connecting system impulse lines and transmitters, having a simple 2 valve configuration, which allows for easy block, bleed and calibration of static pressure transmitter of gauge.

Other mounting options are available on request.



2 Valve Manifold, Remote Mount, NPT

0380 £  
P2VM-SS-8-RM 1/2" 87.55



Maximum Working Pressure:  
414 bar

3 Valve manifold pipe to pipe design for connecting system impulse lines and transmitters. This valve consists of 1/2" NPT female connectors on 54mm centres and 1 equalizer valve and 2 block valves.

Other mounting options are available on request.



3 Valve Manifold, Pipe to Pipe, NPT

0380 £  
P3VM-SS-8-R 1/2" 135.85

5 Valve manifold pipe to pipe design for connecting system impulse lines and transmitters. This valve consists of 1/2" NPT female connectors to suit the inlet connection. This valves provides 2 instrument isolating valves, 2 equalizer valves and 1 bleed valve (for testing).

Other mounting options are available on request.



5 Valve Manifold, Pipe to Pipe, NPT

0380 £  
P5VM-SS-8-R 1/2" 226.20

#### 6,000 psi, Check Valves

Viton Seals

Working Temperature:  
-26°C to +190°C



Maximum Working Pressure:  
400 bar

Tech Sheet 10507

Cracking Pressure:  
0.35 psi



Female, NPT

0292		£
PCV-02-SS-FF	1/8"	58.40
PCV-04-SS-FF	1/4"	61.50
PCV-06-SS-FF	3/8"	69.30
PCV-08-SS-FF	1/2"	102.65
PCV-12-SS-FF	3/4"	241.70
PCV-16-SS-FF	1"	297.15

#### 10,000 psi Check Valves

Working Temperature:  
-26°C to +190°C



Maximum Working Pressure:  
700 bar

Cracking Pressure:  
0.35 psi



Female, NPT.

0292		£
PCV-02-SS-FF-10K	1/8"	131.25
PCV-04-SS-FF-10K	1/4"	138.60
PCV-06-SS-FF-10K	3/8"	156.00
PCV-08-SS-FF-10K	1/2"	231.00
PCV-12-SS-FF-10K	3/4"	543.90
PCV-16-SS-FF-10K	1"	668.65

#### 6,000 psi Rated Ball Valves

Working Temperature:  
0°C to +40°C



Maximum Working Pressure:  
400 bar

Tech Sheet 10508



Female, NPT

0292		£
PBV-2-S-02-FF	1/8"	112.75
PBV-2-S-04-FF	1/4"	112.75
PBV-2-S-06-FF	3/8"	123.70
PBV-2-S-08-FF	1/2"	169.90
PBV-2-S-12-FF	3/4"	268.80
PBV-2-S-16-FF	1"	506.30

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep., Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE