

One Touch All Stainless Steel Push-in Fittings



Working Temperature:
-20°C to +200°C

Maximum Working Pressure:
10 bar
Negative Pressure:
750mm Hg (10Torr)

Material:
Body & Collet: 316 Stainless Steel
O-Ring: FKM

Tube to Connect: PU, Nylon & Teflon
Media: Compressed Air, Steam Water
& Other Compatible Liquids

Tube x Tube Connectors



Equal Straight

0386		£
------	--	---

SSPUC-4	4	21.65
SSPUC-6	6	22.90
SSPUC-8	8	26.45
SSPUC-10	10	29.40
SSPUC-12	12	35.25



Equal Tee

0386		£
------	--	---

SSPUT-4	4	38.75
SSPUT-6	6	40.55
SSPUT-8	8	45.85
SSPUT-10	10	54.10
SSPUT-12	12	64.65

Stem Connectors



Tube x Stem Reducer

0386			£
------	--	--	---

SSPGJ6-4	6	4	17.05
SSPGJ8-4	8	4	17.05
SSPGJ8-6	8	6	17.05
SSPGJ10-6	10	6	19.95
SSPGJ10-8	10	8	19.95
SSPGJ12-8	12	8	19.95
SSPGJ12-10	12	10	21.75



Unequal Straights

0386			£
------	--	--	---

SSPG6-4	6	4	24.10
SSPG8-4	8	4	28.20
SSPG8-6	8	6	28.20
SSPG10-6	10	6	31.15
SSPG10-8	10	8	31.15
SSPG12-8	12	8	37.00
SSPG12-10	12	10	37.00



Equal Bulkhead

0386		£
------	--	---

SSPM-4	4	33.05
SSPM-6	6	36.45
SSPM-8	8	41.75
SSPM-10	10	43.50
SSPM-12	12	47.65

Plug



Tube

0386		£
------	--	---

SSPP-4	4	6.90
SSPP-6	6	7.05
SSPP-8	8	7.60
SSPP-10	10	8.80
SSPP-12	12	10.00



Equal Elbow

0386		£
------	--	---

SSPUL-4	4	27.95
SSPUL-6	6	30.00
SSPUL-8	8	31.75
SSPUL-10	10	35.85
SSPUL-12	12	42.35



Equal Y

0386		£
------	--	---

SSPY-4	4	44.45
SSPY-6	6	46.45
SSPY-8	8	51.70
SSPY-10	10	60.00
SSPY-12	12	70.55



All seals have
FDA Certification