



Jointing Compounds & Sealants

PTFE Thread Sealing Tape



To BS4375

1000		£
PTFE	0.075mm x 1/2" x 10mtr x 0.24g/cm ²	1.25
PTF-40	0.100mm x 1/2" x 10mtr x 0.40g/cm ²	1.70
PTF-80	0.100mm x 19mm x 10mtr x 0.80g/cm ²	3.90

Non flammable thread sealant. Resistant to all acids, alkalis and solvents. Suitable for use with oxygen and potable water.



WRAS, 0.075mm Gauge, 12 Metres, Pack of 10

0241			£
M700WHI1212	White	12	13.20

For use with gas & potable water



Gas Approved, 5 Metres

0241			£
PTFE-GAS	White	12	1.80

To gas board specification.



GAS High Density, 0.20mm Gauge, 5 Metres, Pack of 10

0241			£
M720WHI1205	White	12	17.70

Jointing Paste

Resistant to Gas, Steam, Water, Petrol, Oil and Mineral Acids

- Easy Break
- Lead Free
- Complies to BS6956 Part 5 1992

Temperature Resistance:
A: -40°C to 400°C
B: -40°C to 650°C



Stag A

1092		£
STAGA	400	74.00

Stag B

1092		£
STAGB	500	74.00

Cloth Tapes

High tack adhesive for polythene sheet joining, lagging, heating, ventilation and packaging.



Standard Duct Cloth Tape, 50 metres

0241			£
M24SSIL4850	Silver	48	7.05
M24SBLA4850	Black	48	7.05
M24SWHI4850	White	48	7.05
M24SSIL7250	Silver	72	10.65
M24SSIL9650	Silver	96	14.10

Plate Tapes

Gas board approved to PRS10 high temperature gas flue closure plate sealing tape.



PRS10 Closure Plate Tape, 25 Metres

0241			£
M293GAS5025	Grey	50	13.90

Pipe Tapes

British standard pipe identification tapes as specified under all current building regulations.



Gas ID Tapes, 66 Metres

0241			£
M600GAS3866	Yellow/Black	38	6.10

Boss White & Green

BOSS White Pipe Jointing Compound:
For steam, air, natural gas and non-potable water applications. Conforms to BS6956 Part 5: 1992.



White

1092		£
MIBOSSW400	400	7.45

BOSS Green Potable Water Pipe Jointing Compound:
Suitable for hot and cold potable water services. WRC Approved. Conforms to BS6956 Part 5: 1992.



Green

1092		£
MIBOSSG400	400	12.40

Hank Dressed Hemp



To be used with suitable Jointing Paste.

1092		£
2046-1687	1/2lb	15.15

55 Thread Sealing Cord

Tech Sheet 80



Particularly suitable for metal and plastic threaded fittings. Potable water: WRC listed for use with potable water up to 85°C. Meets BS 6920.KTW recommendation for hot and cold water.

Gas and water: Carries the German DVGW approval (No.DV-5142 AUO 166), together with DIN 30660. Tested in accordance with EN751-2 Class Arp.

- Replaces hemp/tapes and pastes
- Disassembly can be achieved easily with normal tools

0753		£
LOC-483283	50	4.30
LOC-270153	150	11.75

Customers who bought from this page also purchased **Heavy Duty Wire Brushes** – see page 1470



Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep, Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE