



Automotive Tubing & Hose

Corrugated Radiator Hose

Lining: Black heat resistant EPDM rubber.
Reinforcement: Synthetic textile fabric, with steel wire helix, embedded between the layers.
Cover: Black, heat, weather, ozone resistant EPDM rubber.

Temperature Range:
 -40°C to +120°C



1 Metre Lengths

5998	ID	ID mm	OD mm	PSI	£
CRH-78	7/8"	22	30	30	58.95
CRH-1	1"	25	34	30	61.30
CRH-118	1.1/8"	28	36	30	64.90
CRH-114	1.1/4"	32	41	30	72.00
CRH-138	1.3/8"	35	45	30	77.05
CRH-112	1.1/2"	38	47	30	80.10
CRH-134	1.3/4"	44.5	55	30	94.45
CRH-2	2"	51	61	30	116.30

Radiator Hose

Tube: Black SBR (Anti-Freeze) Resistant Rubber.
Reinforcement: Polyester Type Cord 2 Ply.
Safety Factor: 3:1
Cover: Black SBR Heat Abrasion and Weather Resistant.
Application: Vehicle Radiator Hose Ethylene Glycol (Anti-Freeze) Resistant.

Temperature Range:
 -30°C to +100°C



1 Metre Lengths

6000	ID	ID mm	OD mm	PSI	£
RH-78	7/8"	22	30	45	12.75
RH-1	1"	25	34	45	13.25
RH-118	1.1/8"	28	36	45	13.70
RH-1316	1.3/16"	30	38	45	15.85
RH-114	1.1/4"	32	41	45	16.05
RH-138	1.3/8"	35	45	45	16.60
RH-112	1.1/2"	38	47	45	17.80
RH-1916	1.9/16"	40	49	45	18.55
RH-158	1.5/8"	42	52	45	20.70
RH-134	1.3/4"	45	55	45	22.00
RH-178	1.7/8"	48	58	45	25.00
RH-2	2"	51	61	45	25.75
RH-214	2.1/4"	57	67	45	30.10
RH-238	2.3/8"	60	70	45	31.60
RH-212	2.1/2"	63	73	45	35.75
RH-3	3"	76	86	45	46.35
RH-4	4"	102	112	45	68.80

Car Heater Hose SAEJ20R3

Tube: Black Coolant and Heat Resistant Rubber.
Reinforcement: High Strength Polyester yarn 2 Ply.
Cover: Abrasion Ozone and Heat Resistant Rubber.
Application: Automotive O.E.M. and Replacement Market for under bonnet use.

Temperature Range:
 -35°C to +100°C



20 Metre Coils

5998	ID	ID mm	OD mm	PSI	£
2020-9276	3/8"	9.53	19	132	63.55
2020-9284	1/2"	12.5	21	132	78.60
2020-9292	5/8"	16	23	132	88.80
2020-9300	3/4"	19	27	132	157.80
2035-3637	1"	25	36	132	278.75

Cotton Overbraided Fuel Hose DIN 73379 Type B 1983

Tube: Black Fuel and Oil Resistant Rubber.
Cover: Cotton
Application: Fuel Hose for Automotive use (including Unleaded)
Safety Factor: 3:1

Temperature Range:
 -40°C to +85°C Max Peak

Maximum Working Pressure:
 145 psi (10 bar)



20 Metre Coils

5998	ID mm	OD mm	£
COF-3.2	3.2	7	82.60
COF-3.5	3.5	7.5	92.00
COF-4.0	4	9	99.75
COF-4.5	4.5	9.5	109.10
COF-5.0	5	10	112.20
COF-5.5	5.5	10.5	109.10
COF-6.0	6	11	121.55
COF-7.0	7	12	126.20
COF-7.5	7.5	12.5	119.95
COF-8.0	8	13	133.95
COF-9.0	9	14	157.40
COF-10	10	15	169.80
COF-12	12	18	294.50

Petrol Hose, SAEJ30R6

Tube: Black Fuel and Oil Resistant Rubber. For the replacement automotive market.

Reinforcement: Polyester yarn 2 Ply.

Cover: Black Abrasion Oil and Ozone Weather Resistant.

Application: Delivery of Petrol/Diesel and Petroleum based product.



10 Metre Coils

5998	ID	ID mm	OD mm	PSI	£
2020-9318	3/16"	5	11	290	61.20
2020-9326	1/4"	6	12	290	66.20
2020-9334	5/16"	8	14	290	68.70
2020-9359	3/8"	10	18	290	78.95
2035-3645	1/2"	13	23	290	116.30

Diesel Drop Hose

Application: Diesel, air and water delivery up to 20 bar

Tube: Oil resistant rubber alloy

Reinforcement: Synthetic textile braid

Cover: Black weather and ozone resistant with purple stripe

Safety Factor: 3-1

Tech Sheet 10801



50 Metre Coils

5998	ID	OD mm	£
P6320/019	3/4"	28	600.20
P6320/025	1"	34	731.45

Bio Diesel Hose ISO 1307

Tube: Fuel & Oil Resistant, Smooth NBR Rubber.

Burst Pressure: 30 bar

Reinforcement: High Tensile Synthetic Textile.

Minimum Bend Radius: 8mm-50mm and 10mm-65mm

Cover: Abrasion, Ozone, Weather and Oil resistant special synthetic Rubber.


Weight: 8mm-145 g/m and 10mm 170 g/m

Application: Delivery of fuels in internal combustion engines for lubrication and greasing services.

Cut to Length: Max Length 50 Metres
Price per Metre

Working Temperature:
 -35°C to +70°C

Maximum Working Pressure:
 10 bar



Cut to Length, Per Metre

6000	ID mm	OD mm	£
OTR445-10NL-08	8	14	2.80
OTR445-10NL-10	10	16	3.30