



Industrial Hose



Marine Exhaust Hose

Lloyds Approved

Specification: SAEJ2006R1

Application: Wet exhaust hose for marine craft
Tube: Black, exhaust gas, salt water resistant EPDM rubber

Reinforcement: Synthetic textile fabrics, steel wire helix

Cover: Black, corrugated, resistant to heat, salt water, ozone and abrasion EPDM rubber

Safety Factor: 3-1

Temperature Range:
-30°C to +100°C



10 Metre Coils

5998	ID (mm)	OD (mm)	£
SAJ2006R1/032X10	32	41	505.30
SAJ2006R1/038X10	38	47	538.30
SAJ2006R1/045X10	45	54	622.60

40 Metre Coils

5998	ID (mm)	OD (mm)	£
SAJ2006R1/051X40	51	60	2541.30

Medium Duty Smooth Bore PVC Ducting

Extremely light and flexible plasticised PVC. Shock resistant pvc spiral. Abrasion, crushing, chemical agents and weather resistant corrugated outside. Industrial ventilation and airflow systems, suction of dust, air, gases, powders, liquids etc.

Working Temperature:
-10°C to +60°C



Tech Sheet 10509

General Purpose, 10 Metre Coils

5998	ID (mm)	mm	£
URU-25-10	25	30	49.85
URU-32-10	32	35	59.15
URU-38-10	38	45	77.15
URU-51-10	51	60	126.20
URU-76-10	76	100	160.50
URU-102-10	102	140	290.65
URU-152-10	152	180	536.80
URU-203-10	203	400	716.00

Food Quality Suction Discharge Hose

Cold Bend: -45°C

Vacuum: 570mm Hg = 75% at 20°C

Raw materials used have FDA approval for use with foodstuffs.

Applications: Suction and discharge applications of liquids, solids, water etc in the manufacture of foods, beverages and constituent ingredients.

Pressures: Values given are based on the short term burst pressure of the hose at 20°C based on a 3:1 safety factor.

Note: Any increase in temperature above 20°C will result in a decline in working pressure values.

Chemical Resistance: Resistant to most oxidising and reducing agents and diluted acids and alkalis. For more detailed information please contact technical sales.

Temperature Range:
-15°C to +65°C



Clear with White Spiral, 5 Metre Coils

5998	ID (mm)	mm	bar	mm	£
FQSD1-5	1"	2.8	5	130	38.70
FQSD114-5	1.1/4"	3	5	155	49.50
FQSD112-5	1.1/2"	3.4	5	182	60.70
FQSD2-5	2"	4.1	5	235	88.80
FQSD212-5	2.1/2"	4.2	5	290	103.10
FQSD3-5	3"	4.7	5	340	146.20
FQSD4-5	4"	6	4	470	234.70

Clear with White Spiral, 10 Metre Coils

5998	ID (mm)	mm	bar	mm	£
FQSD1-10	1"	2.8	5	130	77.25
FQSD114-10	1.1/4"	3	5	155	99.00
FQSD112-10	1.1/2"	3.4	5	182	121.30
FQSD2-10	2"	4.1	5	235	184.60
FQSD212-10	2.1/2"	4.2	5	290	206.10
FQSD3-10	3"	4.7	5	340	292.35
FQSD4-10	4"	6	4	470	469.35


Medusa Super Elastic Hose

Strong, flexible and smooth, shock and crush resistant PVC spiral. Good in cold climates.

Applications: Medium duty suction and delivery of water, salt water, light chemicals, liquids, sewer purging, sludge, sand and gravel.

Reinforcement: Blue nylon spiral.

Temperature Range:
-20°C to +60°C



Medium Duty Suction & Delivery, 10 Metre Coils

5998	ID (mm)	bar	mm	£
GSE-51-10	2"	15	200	201.00
GSE-63-10	2.1/2"	14	275	259.45
GSE-76-10	3"	12	310	285.90
GSE-102-10	4"	10	410	525.15
GSE-152-10	6"	9	610	831.30

Medium Duty Suction & Delivery, 30 Metre Coils

5998	ID (mm)	bar	mm	£
GSE-51	2"	15	200	603.05
GSE-63	2.1/2"	14	275	778.35
GSE-76	3"	12	310	857.80
GSE-102	4"	10	410	1575.40
GSE-152	6"	9	610	2493.95

Saniflex Premium PVC

Strong, very flexible and smooth white plasticized PVC. Shock resistant galvanised steel spiral wire crushing, abrasion and weather resistant, smooth outside.

Applications: Suction and discharge for sanitary installation in marine and domestic use.

Reinforcement: Galvanised Steel Spiral.



Nitrile Sanitation, 30 Metre Coils

5998	ID (mm)	bar	mm	£
PVCS-20	3/4"	15	50	250.00
PVCS-25	1"	15	60	402.00
PVCS-38	1.1/2"	12	90	549.40