



Hose Reels



Mountable Steel Air Hose Reel

- Heavy ribbed steel plate to ensure strong support.
- Spring located in the middle to ensure stability.
- Four direction non-snag rollers to reduce hose wear abrasion.

- Adjustable guide arm for multi position mounting.
- Special swivel joint for easy maintenance and repair.
- Ball bearing swivel joint structure, largely reducing friction.

Maximum Working Pressure:
20 bar

Tech Sheet
10183



Rubber Air Hose, Spring Rewind, 3/8"

0800 **£**
SAHR-15-38 15m, 3/8" Rubber Air Hose, 3/8" BSPT Connections **223.20**
SAHR-15N-38 No Hose, Capacity 15m, 3/8" Rubber Hose **202.90**

Tech Sheet
10184



Hi-Vis, Spring Rewind, 3/8"

0800 **£**
SAHR-15-38SHV06T 15m, 3/8" BSPT Brass Male **288.50**

Tech Sheet
10188



Rubber Tech, Spring Rewind, 1/2"

0800 **£**
SAHR-15-38SRT06F 15m, 3/8" BSPP Brass Female **286.20**



Swivel Bracket, to suit SAHR-15-38

0800 **£**
SAHR-15-38-SB SAHR-15-38 **21.50**



Swivel Bracket, to suit SAHR-15-12

0800 **£**
SAHR-15-12-SB SAHR-15-12 **25.75**

- Hydraulics
- Hydraulic QRC
- Pneumatic QRC
- Ind. Air Prep., Monitor & Test
- KELM™ Pneumatics
- Pneumatic & Vacuum Equipment
- Valves
- Ring Main Systems
- Adaptors & Fittings
- Stainless Steel
- Malleable Iron
- Hose, Tubing & Couplings
- Clamps & Clips
- Sprays & Adhesives
- Blow Guns & Vacuum
- Wash Down & Fuelling
- Air Tools
- Tools, Hardware & PPE