

Hose Reels

CONAH

Mountable Stainless Steel Hose Reels

- All stainless steel 304 spring rewind hose reels are designed for harsh, corrosive environments or where hygiene is of primary importance.
- Ideally suited for wash down applications in food processing, also for marine and offshore application.

No Hose, Spring Rewind, 3/8"

Maximum Working Temperature:

Maximum Working Pressure:

- All stainless steel swivel assemblies with PTFE washer and viton O-ring for high pressure and high temperature.
- Spring fully enclosed and lubricated.
- · Guide arm adjustable for handling up to 6 positions
- Multi-position ratchet lock keeps hose at desired length. Other configurations available on request.



No Hose, 15m Capacity, 3/8" BSP Outlet

Hydraulics

Pneumatic QRC

Ind. Air Prep Monitor & Test KELM™ Pneumatics

Pneumatio

0800

SSHR-15N-38

+155°C

175 bar

& Vacuum Equipment

Ring Main Systems

Stainless Steel

Sprays & Adhesives

Blow Guns & Vacuum

Air Tools

Tools, Hardware & PPE

0800

SSHR-15-38SB106F 15m, 3/8" BSP Female Outlet

Blue 1 Wire Pressure Wash, Spring Rewind, 3/8"



£

755.35



921.45



Hi-Vis Air & Water, Spring Rewind, 3/8"



15m, 3/8" BSPT Outlet 15m, 1/2" BSPT Outlet

783 20 783.20

Maximum Working Temperature: +100°C

SSHR-15-38SHV08T



Non Marking Wash Down Hose, Spring Rewind, 1/2"







SSHR-15-12SWD08T

15m, 1/2" BSPT Outlet