



## Hose Reels



### Retracta Standard Hose Reels

Redashe Retracta spring rewind hose reels offer performance, reliability and versatility for all popular hose applications. Constructed in high impact UV stabilized polypropylene for all-purpose corrosion free, durability. Retracta reels can be installed indoors or out. They are particularly suited to washdown applications in food processing as an alternative to conventional stainless steel reels. Suitable for wall, floor, bench or overhead installations.

#### Features:

- Superior positive latching mechanism allows the reel to be mounted in any position, with latching of the hose at any length.
- Tough, corrosion free polypropylene construction.
- Lightweight-average just 12kg, easy to install.
- Fully automatic hose rewind for neat and tidy storage.
- Low rewind tension allows for easy hose "pull out".
- Virtually maintenance free.
- Completely serviceable-all parts readily available.
- 5 year warranty (conditions apply).
- Safe storage system that keeps hoses off the floor.



Excluding Hose

**NOTE:** Available for many other applications, with or without hose.

**Hose:** Reinforced PVC

### Retracta Compressed Air Hose Reels, BSP Threads

0122	L mtrs	ID (mm)	Inlet	Outlet	bar		£
AR100	20	10	3/8" Female	1/4" Male	16	Red	412.45
AR200	15	12.5	3/8" Female	3/8" Female	16	Red	436.40

**Hose:** Reinforced PVC

### Retracta Cold Wash Reel 40°C, BSP Threads

0122	L mtrs	ID (mm)	Outlet	bar		£
CW100	15	12.5	Bare End	10	Blue	494.65

**Hose:** Reinforced Rubber

### Retracta Hot Wash Reel 90°C, BSP Threads

0122	L mtrs	ID (mm)	Inlet	Outlet	bar		£
HW100	12	12.5	3/8" Female	3/8" Male	10	Red	560.40

**Hose:** Reinforced Rubber

### Retracta Food Quality Water Reel 95°C, BSP Threads

0122	L mtrs	ID (mm)	Inlet	Outlet	bar		£
FQ100	12	12.5	3/8" Female	1/2" Male	20	Red	591.80

### Retracta Garden Reel

0122	L mtrs	ID (mm)	Inlet	Outlet	bar		£
DR100	18	12.5	3/4" Male	Blank/Nozzle	7	Green	364.65

### Retracta Breathing Air Reels (EN139)

0122	L mtrs	ID (mm)	Inlet	Outlet	bar		£
BH100	15	10	3/8" Female	3/8" Male	12	Red	612.75

### Heavy Duty Spring Rewind Hose Reels




Redashe heavy duty hose reels are engineered for rugged durability. Constructed in heavy gauge powder coated steel for maximum strength and reliability, these spring rewind reels provide years of trouble free service with minimum maintenance. The eight-position roller arm adjusts for wall, overhead and floor mounting while the full flow swivel ensures maximum product delivery.

All models available with or without fitted hose.

**NB:** Hose Not Supplied  
Model shown: SHL-N-550

#### Features:

- Heavy duty steel construction with durable blue powder finish.
- Double supported solid 1" steel axle.
- Multi position roller arm gives full range of mounting positions.
- Four direction non-sag roller guides reduce hose wear.
- 1/4" Steel mounting base for maximum stability.
- Slotted and drilled mounting holes for easy installation.
- Latching of hose at any length.
- All 15 metre (50') capacity; SHL-N-575 22.6 metre capacity.



Suitable for Air, Water, Food, Industry & Diesel - without Hose

0122		L mtrs	£
P-LPL-350	3/8" BSP Female	15	480.50
SHL-N-450	1/2" BSP Female	15	576.90
SHL-N-550	3/4" BSP Female	15	963.85
SHL-N-575	3/4" BSP Female	22.6	1136.50
SHL-N-650	1" NPT Female	15	1136.50

### Heavy Duty, High Pressure Spring Rewind Hose Reels



Designed for high pressure delivery of water, oil and grease. The oil and grease models are ideally suited to lubrication systems in automotive workshops where durability and reliability are paramount. For pressure washer users the 3000 psi/ 150°C rating of the medium pressure water reels provides a solution to the problem of persistent hose damage.

#### Features:

- Heavy duty steel construction with durable blue powder finish.
- Double supported solid 1" steel axle.
- Multi position roller arm gives full range of mounting positions.
- Four direction non-sag roller guides reduce hose wear.
- 1/4" Steel mounting base for maximum stability.
- Slotted and drilled mounting holes for easy installation.
- Latching of hose at any length.
- Fully automatic hose rewind for neat and tidy storage.
- Externally mounted full flow swivel for maximum product delivery.
- All 15 metre (50') capacity.

**NB:** Hose Not Supplied



Suitable for Water, Steam, Oil & Grease - without Hose

0122		£
MPL-N-350	3/8" BSP Female	605.70

- Hydraulics
- Hydraulic QRC
- Pneumatic QRC
- Ind. Air Prep, Monitor & Test
- KELM™ Pneumatics
- Pneumatic & Vacuum Equipment
- Valves
- Ring Main Systems
- Adaptors & Fittings
- Stainless Steel
- Malleable Iron
- Hose, Tubing & Couplings
- Clamps & Clips
- Sprays & Adhesives
- Blow Guns & Vacuum
- Wash Down & Fuelling
- Air Tools
- Tools, Hardware & PPE