



Hose Reels



Stainless Steel, Portable Hose Reels

- Swivel in/out:** 1/2" female x 1/2" female
Width: 622mm
Depth: 680mm
Height: 1100mm
- 304 grade stainless steel construction.
 - Full flow swivel assembly for maximum product delivery.
 - Stainless steel swivel shaft, body nickel plated milled brass.
 - Fitted with viton seals as standard. Swivel has a twin O-Ring design for extended trouble free service.
 - Swept riser assembly for easy hose installation.

- Smooth & positive direct crank design.
- Ideally suited for wash down applications in the food industry, chemical manufacturing, marine & offshore installations.
- Anti-slip rubber feet to prevent movement when extending hose.
- Supplied as a bare reel, hose to suit application at extra cost.



Hose Reel Only

0122					
CCPOR-1345SS	1/2"	7/8"	45	700	909.30
CCPOR-1930SS	3/4"	1.1/8"	30	700	1091.10

Stainless Steel, Manual Side Mount Hose Reel

- The CCMHR-1320 Stainless steel, manual reel offers a hose storage solution for harsh, corrosive, environments or where hygiene is of primary importance. The unit is ideally suited for food processing, marine and offshore applications. Initially designed for marina installations to convey drinking water and other media.
- Constructed in 316 grade stainless steel.
- Direct manual rewind.
- 360° payout and retrieval directions.
- Rolled side discs for additional strength.
- Swept riser assembly for easy hose installation.
- Pedestal side mount only.
- Compact & lightweight design.
- Supplied as a bare reel, hose to suit application at extra cost.

Maximum Working Pressure: 300 psi (20 bar)



Hose Reel Only

0122					
CCMHR-1320SS	1/2"	7/8"	20	300	955.75



A Brand New Concept in Hose Reel Technology

FEATURES & BENEFITS OF THE CONCEPT:

- Eliminates the use of a fixed guide arm in a wall/ceiling mount position.
- Easy to install with no need for post installation adjustments.
- Unique, automatic, 90° vertical rotational span.
- Covers various mounting positions.
- Balanced clock spring produces enough torque to displace the weight of the guide arm.
- Allowing the guide arm to move vertically up and down in a smooth, effortless and fully automatic manner.
- The roller guide and arm/s will always be directly facing the user, giving total control on payout and retrieval.
- Allows the units to be mounted at an increased height.
- Removes the possibility of harm to the operator, passing personnel or damage to machinery compared to low-level units.
- Roller guide arm returns to its rest position after use.
- Sets the reel ready for the next operator.

STANDARD FEATURES:

- Constructed in heavy gauge powder coated steel.
- Finished in a durable, white powder coated gloss finish.
- Latching of hose at any length.
- Fully automatic hose rewind for neat and tidy storage.
- Extended roller guide aperture to ease hose stacking.
- Externally mounted swivel assemblies.
- Viton seals and nylon backup rings as standard.
- Low, Medium and High pressure applications.
- Double supported 1", solid steel axle.
- Pathfinder® Self-adjusting roller guide arm.
- All working parts fully accessible for servicing.
- Floor, wall or ceiling mounting options.
- Suitable for Air, Water, Oil, Diesel and Grease delivery.
- 2-year manufacturer's warranty.
- Swivels 180° through the X axis and 90° through the Y axis.
- Supplied as a bare reel, hose to suit application at extra cost.



Low Pressure, Hose Reel Only

0122				
PFS-915L	3/8"	15	300	577.80
PFS-920L	3/8"	20	300	601.30
PFS-1315L	1/2"	15	300	608.60
PFS-1320L	1/2"	20	300	623.30

Medium Pressure, Hose Reel Only

0122				
PFS-915M	3/8"	15	2250	601.30
PFS-920M	3/8"	20	2250	633.55
PFS-1315M	1/2"	15	2000	630.65
PFS-1320M	1/2"	20	2000	686.40

High Pressure, Hose Reel Only

0122				
PFS-615H	1/4"	15	5000	616.00
PFS-915H	3/8"	15	4000	630.65

