



Lubrication



Hydraulics
Hydraulic QRC
Pneumatic QRC
Ind. Air Prep., Monitor & Test
KELM™ Pneumatics
Pneumatic & Vacuum Equipment
Valves
Ring Main Systems
Adaptors & Fittings
Stainless Steel
Malleable Iron
Hose, Tubing & Couplings
Clamps & Clips
Sprays & Adhesives
Blow Guns & Vacuum
Wash Down & Fuelling
Air Tools
Tools, Hardware & PPE

Dry Film Anti-stick

Use on guide rails on production lines to prevent jams; ideal for use as a non-tainting lubricant on packing and cardboard folding machines. Forms a dry non-staining film, Exhibits excellent friction retardant properties.



Dry PTFE Lubricant

0229



6140003500

400

19.70

Copper Anti-seize

Use on threaded fasteners to prevent seizing during prolonged maintenance intervals, in hostile/high humidity environments and areas subjected to high torque and/or temperatures.

Reduces friction and wear, Good corrosion protection even in highly corrosive environments, Operational temperature range: -30°C to +1100°C.

400ml are Aerosols
500gm are Containers



High Temperature Anti-seize

0229



6190014010

400ml

10.70

6150001030

500gm

14.95

Silicone Lubricant

Use for plastic-to-plastic lubrication, extra slip on chutes or slides, and on push fit pipes. Can also be used as a general mould release agent or as a cutting aid on paper/textile blades. Use on printing lines to reduce ink adhesion.



General Purpose

0229



6190015000

500

5.45

Ambergrease EXL

Use on critical and high load bearings and sliding surfaces. Suitable for use in applications where a longer service interval is required.

Exceptional load carrying capacity: 4-ball weld load >800Kg, Mean Hertz Load 125kg, Timken OK load: 25Kg, Highly visible red, NLGI type 2 grease, Lithium-Calcium Complex thickener.



Extended Life, High Performance Bearing Grease

0229



6150001010

400

10.10

Silicone Anti-stick

High concentration silicone lubricant for more demanding applications with higher loads or increased speeds e.g. robotic picking lines, conveyors, pallet guide rails and close tolerance fitting of large bore pipes.

Ideal for use where high standards of purity are essential, Helps prevent line jams, inhibits adhesive build up on blades and sealers.



Concentrated Silicone Lubricant

0229



6140001500

400

17.90

Dry Moly

Use in higher load applications where PTFE lubricants would fail, but a dry film is still required. Use as a running-in treatment on rolling and sliding bearings.

Use as a lubricant for guides and joints; on wheel bearings on kiln carts; or lubrication of open gears.

Operational temperature range: -150°C to +400°C.



Molybdenum Disulphide Lubricant

0229



6150002000

400

18.45

Due to restrictions imposed by the Transport of Dangerous Goods Act, these products are available for delivery to MAINLAND UK ONLY. For further information please contact our customer service department.

Multi-lube

Versatile lubricant for use in mechanical handling maintenance, Cleans, lubricates and protects against corrosion.



Multi-purpose Lubricant

0229



6170030020

500

5.70

White Spray Grease

Ideal for use on automotive door hinges. Use on runners, guide tracks, and other moving parts, NLGI grade 2 grease in an aerosol



Multi-purpose White Grease

0229



6170030040

500

8.65

Tufcut

Tech Sheet 1036

Tufcut is a range of specialist metal cutting lubricants based on a mixture of lubricants, extreme pressure additives and anti-oxidants. The range has been formulated to offer instant, ready-to-use metal machining products that provide exceptional performance in demanding applications. All the products are suitable for use on a wide range of metals, including stainless and high carbon steels where "right first time" results are required.



Metal Cutting Lubricant

0229



6150006000

350ml Liquid

18.60

6150005500

400ml Spray

16.95

6150006500

300ml Foam

18.50

6150006100

500g Compound

14.70