



## Maintenance Paints



Section 14 – Sprays & Adhesives

### Floor Coating

A ready to use solution for preparing your surface. Removes grease, oil & other contaminations.

Virtually odour free. Non-flammable. 6-8 m<sup>2</sup>/l coverage.



EpoxyShield® Cleaner/Degreaser, 5 Litre Tub

0209



RU-2901.5

63.10

Creates a surface profile that allows for maximum penetration & adhesion for the EpoxyShield® coatings. Uses citric etch formula

to avoid producing dangerous acids or fumes. Will not harm grass or plants.



EpoxyShield® Etching Solution, 5 Litre Tub

0209



RU-108.5

76.00

**Multi-use epoxy resin repair mortar for concrete or stone. Unequalled hardness and epoxy bonding power.** Epoxy Repair Mortar allows fast setting (3-6 hours), granite-hard permanent repairs to be made to badly cracked and worn concrete or stone floors. For use where conventional mortar or other fillers will loosen or fail. Anglo Epoxy Repair Mortar is virtually indestructible and ideal for repairs to factory floors, driveways, worn and broken steps, garage floors, sills, grouting in bolts and railings etc.



Epoxy Repair Mortar

0209



RUS-5180.2.5	2.5kg	42.60
RUS-5180.5.0	5kg	79.65
RUS-5180.25	25kg	290.05

Speed patch give a durable, fast setting repair to damaged floors, frost spalled, eroded and cracked concrete, steps, troughs, ramps covering etc.



Speed Patch

0209



RUS-5150.1	10Kg	67.35
RUS-5150.2	20Kg	117.60

A quick easy way to fill holes in heavily used concrete floors inside and outside. No primer is required - just mix powder with water and pour into the hole. The rapid setting concrete repair bonds to damp or dry surfaces and can be applied at a thickness from feather edge to 100mm



Speed Patch Pourable Grade 25kg

0209



RUS-AXPSP25 119.80

Speed screed smooths uneven, damaged or worn concrete floors. A pour on durable re-surfacing material.

Suitable for interior or exterior use.



Speed Screed 25kg

0209



RUS-AXSS25 112.35

Due to restrictions imposed by the Transport of Dangerous Goods Act, these products are available for delivery to MAINLAND UK ONLY. For further information please contact our customer service department.

Solvent-free Epoxy (2 part) For repairing fine cracks up to 3mm wide.

Dry in 3-4 hours. Coverage: 25 linear metres (2mm wide, 5mm deep).



EpoxyShield® Fine Crack Repair Mortar, 500ml Tub

0209



RU-203010.05

40.50

Mineral-Acrylic. Easy to use - Add water, stir & ready. Traffic allowed after 24hrs.

10kg (1 part) 0.4m<sup>2</sup>. Recoatable after 48 hrs. Note: to be recoated with 7100 Floor coating.



EpoxyShield® Concrete Repair Mortar, 10kg Tub

0209



RU-203012.10

87.95

Rust-Oleum® Asphalt Repair is a durable bitumen-based patch repair product for use on exterior potholed asphalt and concrete. Ideal for potholes in roads, car parks, paths and other bituminous and concrete surfaces.

- Simple to use - no mixing required
- Repairs can be driven over immediately after application
- Ideal for repairs 10 mm - 70 mm
- Coverage approx. 0.5m<sup>2</sup> per 25kg at 24 mm thick
- Withstands heavy traffic



Asphalt Repair 25kg

0209



RUS-5410.25

82.65