



Maintenance Paints



Hard Hat® Maintenance Aerosols

- The quick anti-rust protector.
- Ready to recoat after just 10 minutes, to handle after 30 minutes.
- For new or slightly rusty surfaces.
- Penetrates deeply into the surface & does not give rust a chance.
- Lead & chromate free.



Anti-Rust Primer, 500ml

0209



£

RUS-2169 Red 13.00
RUS-2182 Grey 13.00

Hard Hat® Maintenance Aerosols

- A durable adhesion on galvanized, stainless steel, aluminium, copper, hard PVC, glass & ceramics.
- Ready to recoat after just 30 minutes.
- Unique coverage: 5.5m² per aerosol.
- To recoat with Hard Hat® topcoats.



Sticker Adhesion, 500ml

0209

£

RUS-2102 12.05

Hard Hat® Galvanizing Zincs

- Cathodic protection of bare & galvanized steel.
- Resists 500 hours of salt spray testing (DIN 50021 SS).
- To recoat within one hour, brush version after 4 hours.
- To recoat with Hard Hat® metallic sprays.



Galva Zinc

0209



£

RUS-1085.1 1000 - 18.20
RUS-2185 - 500 15.70

- The super-fast zinc primer.
- Tack free after just 5 minutes, to handle after 10 minutes.
- Ideal for production & construction environments.
- Resists 400 hours of salt spray testing (DIN 50021 SS).



Galva Express, 500ml

0209

£

RUS-2180 13.35

- Zinc coating with sparkling aluminium particles.
- The best compromise between a zinc spray & an aluminium spray.
- Resists 340 hours of salt spray testing (DIN 50021 SS).



Galva Zinc-Aluminium

0209



£

RUS-1017.1 1000 - 19.40
RUS-2117 - 500 15.35

- Appearance similar to new galvanized.
- For touching-up new galvanized.
- Resists 310 hours of salt spray testing (DIN 50021 SS).
- Lower zinc contents, more aluminium.



Galva Plus, 500ml

0209

£

RUS-2120 13.35



Zinc Gloss

	2185 / 1085.1 GALVA ZINC	2180 GALVA EXPRESSE	2117 / 1017.1 GALVA ZINC-ALU	2120 GALVA PLUS
Appearance	Matt grey	Matt grey	Sparkling aluminium	Aluminium gloss
Zinc %	90%	68%	80%	54%
Aluminium %	0%	1%	10%	23%
Salt spray test	500 hrs.	400 hrs.	340 hrs.	310 hrs.
Tack free	10 min / 15 min	5 min	20 min / 30 min	15 min
To handle	30 min / 2 hrs.	10 min	60 min / 3 hrs.	60 min
Heat-resistant	450°C / 100°C	350°C	450°C / 100°C	150°C
Main advantage	Best protection	Quick drying	Good protection + finish	Finish like new galvanized

Due to restrictions imposed by the Transport of Dangerous Goods Act, these products are available for delivery to MAINLAND UK ONLY. For further information please contact our customer service department.

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep., Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE