



Thread Sticks

Section 14 – Sprays & Adhesives

Threadlocker Sticks

- Effective on all types of metal threaded fasteners. Recommended where disassembly is required. Machine tools and presses, pumps and compressors, mounting bolts and gear boxes.
- For use on threads up to M50.
- Functional strength 6 hours.
- Long term temperature resistance +150°C.



248, Medium Strength

0753		£
LOC-248	19	17.35

Thread Sealant Stick

- Recommended for all coarse metal pipe threads where disassembly is required. Ideal for use in a broad range of industries including chemical, processing, waste water treatment and automotive.
- For use on threads up to 3".
- Substrate to be sealed: Metal.
- Instant low pressure seal.
- Low disassembly strength.
- Long term temperature resistance +150°C.



561, Instant Bonding

0753		£
LOC-561	19	11.20

243 Threadlocker

- Particularly suitable on all metal threaded fasteners. Prevents loosening on vibrating parts such as pumps, motor mounting bolts, gear boxes or presses. Recommended for use where disassembly with hand tools is required for servicing and where parts are contaminated with oil.
- Resists vibration
 - Single part – clean and easy to apply
 - Can be used on all sizes of fasteners – reduces inventory costs
 - Seals threads allows through-hole tapping



Medium Strength

0753		£
LOC-135279	10	9.50
LOC-135278	50	42.75

Anti-Seize Sticks

- Copper based anti-seize for screws, nuts, pipes, heat exchangers etc.
- Sold lubricating agent containing copper and graphite.
- N.L.G.I. Class 1

Temperature Range:
-30°C to +930°C



8065, C5-A Copper, High Temperature

0753		£
LOC-8065	20	9.30



268, High Strength

0753		£
LOC-268	19	17.33

270 Threadlocker

- Particularly suitable for use on all metal fasteners (including stainless steels and those with protective coatings such as Zinc) where regular removal for maintenance is not required. Recommended for permanently locking studs on engine blocks and pump housings.
- Resists vibration
 - Single part – clean and easy to apply
 - Can be used on all sizes of fasteners – reduces inventory costs
 - Seals threads allows through-hole tapping



High Strength

0753		£
LOC-267380	10	9.35
LOC-232515	50	41.85

Due to restrictions imposed by the Transport of Dangerous Goods Act, these products are available for delivery to MAINLAND UK ONLY. For further information please contact our customer service department.