



# Sealant, Retainer, Super Glue & Tape



Hydraulics
Hydraulic QRC
Pneumatic QRC
Ind. Air Prep., Monitor & Test
KELM™ Pneumatics
Pneumatic & Vacuum Equipment
Valves
Ring Main Systems
Adaptors & Fittings
Stainless Steel
Malleable Iron
Hose, Tubing & Couplings
Clamps & Clips
Sprays & Adhesives
Blow Guns & Vacuum
Wash Down & Fuelling
Air Tools
Tools, Hardware & PPE

## 572 Low Strength Slow Cure Pipe Seal

- This product is designed for the locking and sealing of metal pipes and fittings.
- The product cures when confined in the absence of air between close fitting metal surfaces and prevents loosening and leakage from shock and vibration.
- The thixotropic nature reduces the migration of liquid product after application to the substrate.



0753		£
LOC-229360	50	21.35

## 574 Flange Sealant

- Seals close fitting joints between rigid metal faces and flanges.
- The product cures when confined in the absence of air between close fitting metal surfaces.
- Provides resistance to low pressures immediately after assembly of flanges.
- Typically used as a form-in-place gasket on rigid flanged connections, e.g. gearbox and engine casings, etc.
- The thixotropic nature reduces the migration of liquid product after application to the substrate.



0753		£
LOC-267437	50	27.95

## 518 Flexible Fast Cure

- This product is a single component, medium strength, anaerobic sealant which cures when in the absence of air between close fitting metal surfaces.
- Typical applications include sealing close fitting joints between rigid metal faces and flanges.
- Provides resistance to low pressures immediately after assembly of flanges.
- Typically used as a form-in-place gasket on ridged flanged connections, e.g. gearbox and engine casings, etc.
- The thixotropic nature reduces the migration of liquid product after application to the substrate.



0753		£
LOC-229875	50	31.30

## 5400 Health & Safety Pipe Sealant

- No hazard symbols, no risk phrases
- White material safety data sheet
- No need for COSHH assessment
- WRAS Approved



0753		£
LOC-1545634	50	26.15
LOC-1546964	250	106.15

## 603 Retainer

Particularly suitable for retaining close fitting cylindrical parts (up to 0.1mm gap), and for use on cylindrical fitting parts where thorough degreasing is not possible.

Tested and approved for use on bearings.

- High and moderate strength products – can carry high loads and eliminate fretting
- Fill all voids – prevent corrosion
- Reduce the need for close tolerances
- 100% contact – load and stress is distributed evenly over the joint



For Retaining Cylindrical Parts

0753		£
LOC-229873	10	9.50
LOC-135280	50	42.75

## 638 Retainer

Particularly suitable where dynamic axial and radial loads are present. Recommended for retaining shafts, gears, pulleys and similar cylindrical parts.

- High and moderate strength products – can carry high loads and eliminate fretting
- Fill all voids – prevent corrosion
- 100% contact – load and stress is distributed evenly over the joint



Resistant to Radial & Axial Loads

0753		£
LOC-234795	50	40.75

Due to restrictions imposed by the Transport of Dangerous Goods Act, these products are available for delivery to MAINLAND UK ONLY. For further information please contact our customer service department.