



Wash Down Equipment



High Pressure Spray Nozzles

Stainless Steel 1/4" Male thread with a hardened steel insert for longer life and better accuracy, suitable for single and double lances.



Stainless Steel, 1/4" BSPT Male

1369		@50bar LPM	@100bar LPM	@150bar LPM	£
2020-2982	0°	8	11.3	13.8	12.10
2020-2990	0°	8.7	12.4	15.2	12.10
2020-3014	0°	9.6	13.6	16.7	12.10
2020-3089	15°	8	11.3	13.8	12.10
2020-3105	15°	8.7	12.4	15.2	12.10
2020-3113	15°	9.6	13.6	16.7	12.10
2020-3139	25°	8	11.3	13.8	12.10
2020-3147	25°	8.7	12.4	15.2	12.10
2020-3154	25°	9.6	13.6	16.7	12.10
2020-3162	40°	8	11.3	13.8	12.10
2020-3188	40°	8.7	12.4	15.2	12.10
2020-3204	40°	9.6	13.6	16.7	12.10

Brass 1/4" BSPT Male

1369	£
2021-8061	10.25

High Pressure Water Quick Release Coupling



Maximum Working Pressure: 210 bar

Interchangeable with: Nito High Pressure Water Coupling 40 Series Water Coupling



Female Carrier, BSPP

1369		£
PWQRC-38	3/8"	20.00



Female Probe, BSPP

1369		£
PWQRP-38	3/8"	8.90

Pressure Washer Adaptors

Maximum Flow: 40 lpm



Maximum Temperature: +140°C

Maximum Pressure: 210 bar

BSPP Male x Female M22 x 1.5

1369		£
PWAB-14M	1/4"	14.90
PWAB-38M	3/8"	15.70
PWAB-12M	1/2"	15.70

Maximum Flow: 40 lpm



Maximum Temperature: +140°C

Maximum Pressure: 210 bar

BSPP Female x Male M22 x 1.5

1369		£
PWAA-14F	1/4"	12.05
PWAA-38F	3/8"	12.25



Maximum Temperature: +90°C

Maximum Pressure: 250 bar

Compact Swivel Coupling Brass, 3/8" BSPP

1369		£
21-049		20.00

Maximum Flow: 40 lpm



Maximum Temperature: +140°C

Maximum Pressure: 210 bar

BSPP Female x M22 x 1.5 Female

1369		£
PWAB-14F	1/4"	17.70
PWAB-38F	3/8"	17.70




Maximum Temperature: +130°C

Maximum Pressure: 250 bar

Brass Swivel Coupling Standard, BSPP

1369		£
21-051	1/4"	59.95
21-050	3/8"	59.95
21-052	1/2"	59.95



Maximum Temperature: +140°C

Maximum Pressure: 210 bar

BSPT Male x M22 x 1.5 Male

1369		£
PWAA-14M	1/4"	10.20