



Electrical Transfer Pumps



Professional Diesel Transfer Pumps

Only suitable with diesel or biodiesel up to B30. Pumping speeds 50, 80 or 100 L/min. 230V or 110V. Direct drive, self priming, vane pumping units. 1" BSPF ports. Switch & 2m long mains cable. Integral filter & bypass. Weatherproof to IP55 for outdoor use. Continuously rated motor with thermal cut out. Full range of spares available.



| 0225 | | | £ |
|-------------|------|-----|--------|
| SPT60A | 230V | 50 | 240.75 |
| SPT70K-110 | 110V | 50 | 470.25 |
| SPT80A | 230V | 80 | 330.60 |
| SPT80K-110 | 110V | 80 | 692.20 |
| SPT100A | 230V | 100 | 632.20 |
| SPT100K-110 | 110V | 110 | 890.00 |

Portable Oil Pump

Portable battery operated transfer pump 12 volt. Suitable for oil, water, antifreeze and diesel/gasoil. On/off switch, suction lift 1.5m, total head 20m. **Maximum run Time: 30 mins.**

Tech Sheet 1175



| BSPP | 0225 | | | | £ |
|-----------|------|-----|----|--------|---|
| 2019-9428 | 3/8" | 12V | 14 | 508.25 | |
| OIL.GEL24 | 1/2" | 24V | 14 | 508.25 | |

230V Professional Diesel Pump Kit

Only suitable with diesel or biodiesel up to B30. Manual operated on/off switch. Pumping speeds choose 45 or 75 L/min option. Meter accuracy of +/- 2%. 4 digit resettable register. 8 digit non resettable totaliser. Weatherproof to IP55. Integral filter & bypass valve. 230V continuously rated motor with thermal cut out. 4m delivery hose. Choose manual or automatic nozzle options. Self priming pump unit. Dims 300mm H x 350mm W x 500mm D (including nozzle). **45 Litres Per Minute:** Ideal to fill cars/vans vehicles with small fuel tanks. **75 Litres Per Minute:** Ideal to fill vehicles with large fuel tanks



| 45 Litres per Minute | | 0225 | | £ |
|----------------------|------------------|------|--|--------|
| ECON45.MAN | Manual Nozzle | | | 553.15 |
| ECON45 | Automatic Nozzle | | | 676.10 |

| 75 Litres per Minute | | 0225 | | | £ |
|----------------------|-----------------------|------|--|--|--------|
| ECON75.MAN | 230V Manual Nozzle | | | | 752.30 |
| ECON75 | 230V Automatic Nozzle | | | | 880.60 |

Battery Operated Fuel Pump

Ideal for mounting into plant equipment where space is limited. Steel foot mounting plant. 3/4" BSPF female inlet & outlet ports. Built in bypass. **Maximum run time: 30 mins**



Tech Sheet 1169

| For use with Diesel/Gasoil | | | |
|----------------------------|-----|----|--------|
| 0225 | | | £ |
| 2033-5287 | 12V | 40 | 221.70 |
| 2033-5303 | 24V | 40 | 221.70 |
| 12P60 | 12V | 60 | 641.05 |
| 24P60 | 24V | 60 | 641.05 |

Portable Fuelling Kit c/w 200L Tank

Only suitable with diesel, gasoil & biodiesel up to B30. Strong & lightweight diesel tank - only 15kgs when empty. Impact resistant polytuff construction for long working life. Fitted with a 12V 40L/min pump, auto nozzle, 4m x 3/4" hose. Supplied with 4m long cable & croc clips for easy connection. Max. run time 30mins. Anti-slosh breather to prevent any spillages whilst in transit. Safety bottom fill drop tube to prevent overfilling. Mounting bracket allows nozzle to be padlocked. Dimensions: 1110mm D x 640mm W x 550mm H. ADR exempt



| 12 Volt | | 0225 | | £ |
|---------|----|------|--|--------|
| T200P | 40 | | | 818.20 |

Air Operated Transfer Pumps

Polypropylene Air Operated Diaphragm Pump

1:1 ratio. Max operating pressure 116 psi/8 bar. Rugged Polypropylene body. Viton diaphragm. Maximum solids pumped = 3mm dia. Air inlet 1/4". Suitable for Adblue® & antifreeze.



| BSPP | | 0225 | | | £ |
|----------|------|---------------------|--|--|--------|
| ADP.60PV | 3/4" | 60 LPM, Viton Seals | | | 501.80 |

Aluminium Air Operated Diaphragm Pump

1:1 ratio. Max operating pressure 116 psi/8 bar. Rugged aluminium body. Nitrile diaphragm. Maximum solids pumped = 3mm dia. Air inlet 1/4". 325mm H x 255mm W x 210mm D



Tech Sheet 10578

| BSPP | | 0225 | | | £ |
|----------|------|-----------------------|--|--|--------|
| ADP.60AV | 3/4" | 60 LPM, Viton Seals | | | 572.35 |
| ADP.90AN | 1" | 90 LPM, Nitrile Seals | | | 726.20 |

Pneumatic Pumps



Tech Sheet 2053

| Oil Pumps | | 0122 | Ratio | | £ |
|-----------|-------|--------------------|-------|--|--------|
| J100 | 01:01 | 940mm Suction Tube | | | 237.40 |
| J300S | 03:01 | 270mm Suction Tube | | | 223.50 |
| J500S | 05:01 | 270mm Suction Tube | | | 216.50 |