



Greasing & Lubrication Equipment

CISSON

High Pressure Hose & Accessories



Reinforced Hose 600 to 840 bar, 10 Metre Coil

0382	ID (mm)	OD (mm)		£
LU-1710	4	8.75	None Filled	102.05
LU-1720	4	8.75	Grease Filled	145.30
LU-1730	6.3	11.3	None Filled	127.15



Straight Inserts, Steel Zinc Plated

0382	ID (mm)	OD (mm)	£
LU-1740	4	8.75	4.40
LU-1750	6	8.75	4.70



Straight Inserts, Stainless Steel

0382	OD (mm)	OD (mm)	£
LU-1760SS	6	8.75	18.70
LU-1770SS	8	11.3	8.80



90° Inserts, Steel Zinc Plated

0382	OD (mm)	OD (mm)	£
LU-1780	6	8.75	10.55
LU-1790	8	11.3	17.65



Ferrule, Zinc Plated

0382	OD (mm)	£
LU-1800	8.75	5.15
LU-1810	11.3	11.80



Ferrule, Stainless Steel

0382	OD (mm)	£
LU-1820SS	8.75	18.70
LU-1830SS	11.3	38.35

Lubrication & Pumping Equipment

Three Inch Air Motor, provides more power to create better flow.
 NXT Air Valve, designed to reduce icing in continuous use applications and uses less air than competitive pumps for better efficiency. Easy to repair or replace without tearing down internal pump components for less downtime.

Built-In Thermal Relief and Inlet Strainer, built-in thermal relief protects your equipment from thermal expansion without the need to buy and install an additional kit. Inlet strainer (oil only) is built-in to protect pump from contaminants that can damage your pump.

Modular Air Valve, air inlet and exhaust locations are easy to configure with just four bolts for simple, hassle free installations.



Connections:

Air Line 1/4" BSP
 Fluid Outlet 1/2" BSP
 Inlet 1" BSP
 900mm plastic down tube (can be cut down as required).

LD Range Oil Pumps

0382	Ratio	LPM	£
24G581	3:1	9.8	642.25
24G593	5:1	7.6	676.95



Wall Mount Bracket

0382	To Suit	£
24F910	24G5 Series Pumps	179.35

Spring Greasers

1/8" BSP.
 On demand grease delivery. Easy visual level check. Simple and robust design. Polycarbonate base.

Working Temperature:
 -23°C to +121°C



LubeSite
Systems, Inc.

Refillable

0382	gm	£
SL202	28	52.75
SL205	56	61.35
SL260	170	124.05

Remote Grease Systems

Contents:

- 1 x 1/8" BSP 2 way block
- 2 x 1/8" BSP straight grease nipples
- 4 x 1/8" BSP x 6mm straights
- 2 x M8 x 1 straight compression fittings
- 30 metre of 6 x 3mm semi rigid black nylon tube.



2 Point

0382

£

BAT03

131.95

Contents:

- 1 x 1/8" BSP 6 way block.
- 6 x 1/8" BSP straight grease nipples.
- 6 x M6 x 1 x 6mm straight compression fittings.
- 6 x 1/8" BSP x 6mm straight compression fittings.
- 30 metre of 6 x 3mm semi rigid black nylon tube.



6 Point

0382

£

BAT06

158.50

Manual Grease System

Contents:

- 1 x 1 litre manual pump.
- 1 x 4 way grease block.
- 1 x 81-5261-1/4 x 6mm straight.
- 8 x 1/8" BSP x 6mm fitting.
- 30 metre coils of 6 x 3 semi rigid black nylon tube.
- 6 x 1 way pipe clips.



Suitable for soft grease NLGI NO 000,00,0
 For use on small machinery, direct feed on to bearings.
 1.00cc delivery per stroke.
 Max discharge pressure 150 bar.



4 Point

0382

£

PROG12

630.35

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep., Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE