



## Greasing & Lubrication Equipment



### Grease Hoses



Maximum Working Pressure:  
400 bar  
Burst Pressure:  
900 bar



Single Steel Braid Rubber Hose,  
Male Thread, BSPP

0088			£
2017-3654	1/8"	12"	6.55
2017-3662	1/8"	18"	6.55



Nylon Braid Hoses Polyamide  
Coated, Male Thread, BSPP

0088			£
2017-3670	1/8"	12"	5.05
2017-3688	1/8"	18"	5.65

Rigid Stem with  
4 Jaw Connector

0088		£
2017-3720		10.15

### Lithium No.2 Grease Cartridge

Multi purpose bearing grease No.2 consistency  
for conventional applications.



0088		£
2017-6780	400	7.40

## Pressure Hoses

### Pressure Hoses



Working Temperature:  
-40°C to +100°C



For use with Oil, 1/2" BSPP  
Male/Female x 1/2" ID 1 Wire Hose

0300			£
1BMF0808-600	2320	600	7.90
1BMF0808-800	2320	800	8.85
1BMF0808-2000	2320	2000	14.80
1BMF0808-4000	2320	4000	18.60
1BMF0808-10000	2320	10000	54.65



For use with Grease, 1/4" BSPP  
Male/Female x 1/4" ID 2 Wire Hose

0300			£
2BMF0404-600	5800	600	5.60
2BMF0404-1500	5800	1500	9.40
2BMF0404-4000	5800	4000	19.90
2BMF0404-10000	5800	10000	45.10



For use with Air & Water, 3/8" BSPP  
Male/Female x 3/8" ID Hose

0300			£
AW-R6-600	1620	600	8.65
AW-R6-2000	1620	2000	13.40
AW-R6-4000	1620	4000	20.30
AW-R6-10000	1620	10000	41.05

### Long Life Flexible Oil Lines



Working  
Temperature:  
-40°C to +100°C



R1, 1/4" BSPP Female/Female x  
1/4" ID 1 Wire Hose

0300			£
1BFF0404-600	3260	600	4.75
1BFF0404-750	3260	750	5.25
1BFF0404-1000	3260	10000	6.05



Working  
Temperature:  
-40°C to +90°C



Thermoplastic, 1/4" BSPP Female/  
Female x 1/4" ID 1 Wire Hose

0300			£
7BFF0404-600	2755	600	6.35
7BFF0404-750	2755	750	7.05
7BFF0404-1000	2755	10000	9.05

### Workshop Manual Pressure Test Pump

Designed for pressure testing hoses, pipework  
radiators & boilers etc. Can use with water or oil for  
testing. Comes with a gauge to monitor the pressure  
in the line. Fills the line you are testing with fluid from  
the reservoir. Working pressure: 290psi  
(20 bar). Comes complete  
with 2m delivery hose.  
1/2" BSPM connector.  
Brass pump with anodised  
aluminium piston.  
Housed in a 5 litre  
capacity steel reservoir.  
Delivery per stroke: 12cc.



0225	£
PTP	243.35

Hydraulics

Hydraulic  
QRC

Pneumatic  
QRC

Ind. Air Prep,  
Monitor  
& Test

KELM™  
Pneumatics

Pneumatic  
& Vacuum  
Equipment

Valves

Ring Main  
Systems

Adaptors  
& Fittings

Stainless  
Steel

Malleable  
Iron

Hose, Tubing  
& Couplings

Clamps  
& Clips

Sprays &  
Adhesives

Blow Guns  
& Vacuum

Wash Down  
& Fuelling

Air Tools

Tools,  
Hardware  
& PPE