



SYNAIRGY AIR COMPRESSORS



Maximum Working Pressure: 8 bar



Working Temperature: -5°C to +35°C

Direct Drive Compressor

Tech Sheet 10438

This range of SYNAIRGY Oil Lubricated Air Compressors are built with performance and reliability in mind. They have a robust, strong design for many trade applications with the advantages of a compact construction and lightweight design.

Its easy to use operation along with excellent safety characteristics and low noise levels make it perfect for all typical applications including: Paint Spraying, Inflating, Blowing, Nailing, Air Tools and other applications where compressed air is required.

All units are fitted with safety valve and pressure regulator with gauges for controlled outlet air pressure.

Belt Driven Compressor

Tech Sheet 10439

The SYNAIRGY Belt Driven Air Compressor is built with performance and reliability in mind. These units are designed with industrial and commercial users in mind, with the air capacity and power to drive many of the most commonly used air compressor tools. Its easy to use operation along with excellent safety characteristics and low noise levels make it perfect for all typical applications and will satisfy the air requirements of most garages, small factories, workshops and farms where compressed air is required.

All units are fitted with safety valve and pressure regulator with gauges for controlled outlet air pressure.



Lubricated

0393

CFM

LPM

bar

HP

Litres

⚡

£

SACDD-24	7	198	8	2	24	240/50	142.35
SACDD-50	7	198	8	2	50	240/50	170.35

Lubricated

0393

CFM

LPM

bar

HP

Litres

⚡

£

SACBD-100	7	198	8	3	100	240/50	490.00
-----------	---	-----	---	---	-----	--------	--------