



Hydraulic Hose Range

Page Tech Sheet **5010**

Section 1 – Hydraulics

Oil Return/Fuel Hose SAE 100R6

100R6 Hose

Application:

- Low pressure hydraulic applications, for use with push style fittings. See page 36

Specification:

- SAE100 R6, exceeds EN854

 **Working Temperature:**
-40°C to +100°C

Construction:







- Inner tube: oil resistant synthetic rubber (NBR)
- Reinforcement: 1 single textile yarn braid
- Outer cover: oil & weather resistant synthetic rubber

Recommended Fluids:







- Hose suitable for petroleum based hydraulic oil and water-glycol based fluids, air and water

Available per 1mtr







50 Metre Coils, Blue

	0303						
Hydraulic QRC	100R6-04-B-50	1/4"	13.5	28	65	112	144.10
	100R6-06-B-50	3/8"	16.7	28	75	112	226.95
Pneumatic QRC	100R6-08-B-50	1/2"	20.6	28	100	112	310.85







25 Metre Coils, Blue

	0303						
KELM™ Pneumatics							
Pneumatic & Vacuum Equipment	100R6-12-B-25	3/4"	27.8	21	150	84	233.20
	100R6-16-B-25	1"	32.5	20	205	80	303.80

50 Metre Coils, Green

	0303						
Stainless Steel	100R6-04-G-50	1/4"	13.5	28	65	112	144.10
	100R6-06-G-50	3/8"	16.7	28	75	112	226.95
Malleable Iron	100R6-08-G-50	1/2"	20.6	28	100	112	310.85

25 Metre Coils, Green

	0303						
Clamps & Clips							
Sprays & Adhesives	100R6-12-G-25	3/4"	27.8	21	150	84	233.20
Blow Guns & Vacuum	100R6-16-G-25	1"	32.5	20	205	80	303.80

