



Hydraulic Accessories



Plugs

- Material: Elastomer, soft polyurethane.
- Ideal for keeping threads clean when spraying tanks.

Temperature:
+100°C

Maximum Working Pressure:
2-3 bar

Tech Sheet
10474



Screw-in Protection Plugs, BSPP

0027		£
K5618018	1/8"	0.15
K5618014	1/4"	0.35
K5618038	3/8"	0.35
K5618012	1/2"	0.45
K5618034	3/4"	0.55
K5618100	1"	0.60

Press-in Plugs

- Material: Thermoplastic polyamide 66.
- Air Filter: Polyurethane foam.
- Filter fineness 50µm.

NOTE: Not suitable for pressurised tanks.

Tech Sheet
10475



With Ventilation with Rubber O-Ring

0027			£
K562223018	18	8	2.10
K562323020	20	8	2.50
K562423026	26	9.5	2.90

Without Ventilation with Rubber O-Ring

0027			£
K562213020	20	8	2.35
K562213030	30	9.5	3.70

Plugs with Magnets

- Material: Aluminium.

NOTE: Mounted on the bottom of tanks to attract metal parts.

Tech Sheet
10476



Aluminium, BSPP

0027			£
K562621014	1/4"	19	4.10
K562624038	3/8"	22	5.85
K562630012	1/2"	27	5.95
K562636034	3/4"	34	10.30
K562642100	1"	40	13.50

Vent Screws

- Material: Thermoplastic polyamide 66.
- Air Filter: Polyurethane foam.
- Fluid Compatibility: Mineral based oils and solvents.

Temperature:
+100°C

Tech Sheet
10477



With Oil Fill Symbol

0027		£
K5634136038	3/8"	2.80
K5634141012	1/2"	3.20
K5634147034	3/4"	3.70
K5634152100	1"	4.45
K5634163114	1.1/4"	5.95
K5634163112	1.1/2"	6.30
K56341361615	M16 x 1.5	2.75
K56341411815	M18 x 1.5	2.90
K56341412015	M20 x 1.5	3.10
K56341412215	M22 x 1.5	3.20

With Oil Fill Symbol & Filter

0027		£
K5634236038	3/8"	3.20
K5634241012	1/2"	3.70
K5634247034	3/4"	4.10
K5634252100	1"	5.00
K5634263114	1.1/4"	6.35
K5634263112	1.1/2"	6.65
K56342361615	M16 x 1.5	3.20
K56342411815	M18 x 1.5	3.50
K56342412215	M22 x 1.5	3.90

Tech Sheet
10478



With Splash Guard, Filter & Oil Symbol, BSPP

0027		£
K563630014	1/4"	2.60
K563630038	3/8"	2.75
K563630012	1/2"	3.20

Vent Screws with Dipstick

- Material: Black thermoplastic polyamide 66.
- Filter: Polyurethane foam 50µm.
- Dipstick: Galvanized steel.
- Fluid Compatibility: Mineral based oils and solvents.
- Dipstick Length: 200mm except non-return & splash back 195mm.

Tech Sheet
10479



With Vent, Filter & Fill Symbol

0027		£
K5654236038	3/8"	4.30
K5654241012	1/2"	4.80
K5654247034	3/4"	5.20
K5654252100	1"	6.30
K56542412015	M20 x 1.5	4.70

Tech Sheet
10480



With Non-return Valve & Non-return Symbol, BSPP

0027		£
K563830014	1/4"	3.75
K563830038	3/8"	3.90
K563830012	1/2"	4.30

Brass Vent Screws

- Material: Housing & cap in brass filter in galvanized steel wire 50-60 µm.

Tech Sheet
10481



Filter & Vent, BSPP

0027		£
K564020014	1/4"	4.85
K564024038	3/8"	6.10
K564030012	1/2"	6.70

Tech Sheet
10482



Non-return Valve & Vent, BSPP

0027		£
K564220014	1/4"	4.85
K564224038	3/8"	5.90
K564230012	1/2"	6.70