



Glycerine Gauges & Accessories



All Stainless Steel Gauges, 1/4" Bottom Connection



1/4" BSPP

0021	mm	PSI	bar	£
SSG63-001BG	63	0-15	0-1	66.95
SSG63-004BG	63	0-60	0-4	66.95
SSG63-012BG	63	0-200	0-12	66.95
SSG63-025BG	63	0-400	0-25	66.95
SSG63-060BG	63	0-1000	0-60	66.95
SSG63-200BG	63	0-3000	0-200	66.95
SSG63-400BG	63	0-6000	0-400	66.95

All Stainless Steel Gauges, 1/2" Bottom Connection



1/2" BSPP

0021	mm	PSI	bar	£
SHG100-002BG	100	0-30	0-2	228.20
SHG100-006BG	100	0-100	0-6	228.20
SHG100-016BG	100	0-250	0-16	228.20
SHG100-040BG	100	0-600	0-40	228.20
SHG100-100BG	100	0-1500	0-100	228.20
SHG100-250BG	100	0-4000	0-250	228.20
SHG100-600BG	100	0-9000	0-600	228.20

All Pressure Gauges can be supplied with a Calibration Certificate at a nominal charge. Please call our Business Development Team for Price & Delivery.

For Glycerine Gauges & Accessories see pages 439-440

All Stainless Steel Gauges, 1/4" Centre Back Connection



1/4" BSPP

0021	mm	PSI	bar	£
2038-8583	40	0-200	0-12	50.45
2038-8591	40	0-300	0-20	50.45
2038-8609	40	0-600	0-40	50.45
2038-8625	40	0-900	0-60	50.45
2038-8633	40	0-4000	0-250	50.45
2038-8534	63	0-200	0-12	73.40
2038-8567	63	0-900	0-60	73.40
2038-8575	63	0-4000	0-250	73.40

All Stainless Steel Gauges, 1/2" Centre Back Connection



1/2" BSPP

0021	mm	PSI	bar	£
2038-8435	100	0-200	0-12	198.90
2038-8443	100	0-300	0-20	198.90
2038-8450	100	0-600	0-40	198.90
2038-8476	100	0-4000	0-250	198.90

Back Rubber Gauge Protectors



OPEN



CLOSED

0021	Open	£
G63-OB	Open	26.90
G63-CB	Closed	26.90

Gauge Snubbers

Gauge Snubbers are a great way of protecting gauges from damage, with sudden impact pressure i.e. when full line pressure is introduced to the gauge damage can occur. With the use of the snubber the gauge will be protected.



Working Pressure: 20-300 bar

Tech Sheet 28



High Pressure

0021	Male	Female	£
130.4	1/4"	1/4"	30.40
130.3	3/8"	3/8"	33.95
130.2	1/2"	1/2"	45.30



Working Pressure: 0-20 bar



Low Pressure

0021	Male	Female	£
131.8	1/8"	1/8"	12.10
131.4	1/4"	1/4"	12.15
131.3	3/8"	3/8"	16.80
131.2	1/2"	1/2"	20.85

Bleeder Valve



Temperature Range: -20°C to +85°C



Pressure Rating: 10 bar



BSPP

0021	£
124.8	1/8" 10.90
124.4	1/4" 10.90
124.3	3/8" 11.65

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep., Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE