



## Hydraulic Oils



Section 1 – Hydraulics

### ISO 32 Hydraulic Oil

Quality mineral hydraulic oil with good anti-wear performance, oxidation resistance, corrosion protection, low pour, air release and anti-foam properties. Conforms to DIN 51524 11.

Tech Sheet  
544



25 Litre Drum

0026



25



143.40

2020-0333

### 10W Hydraulic Oil

Hydraulic Oil 10W is a high performance hydraulic oil formulated from solvent refined paraffinic base oils & high performance additives designed to meet a wide range of heavy duty hydraulic equipment requirements.

Benefits include: Good deposit control, good anti-sludge & varnish resistance, excellent anti-wear & corrosion protection.

Oxidation stability, dispersant/detergent properties & wide temperature range.

High viscosity index promotes high oil pressure.

Conforms to API: SF/CD & MIL-L-2104C.

Tech Sheet  
3147



25 Litre Drum

0026



25



172.35

10W OIL

### ISO 46 Hydraulic Oil

Hydraulic oil 46 is blended to ISO 46 viscosity grade requirements & is suitable for use in a wide range of mobile & static hydraulic equipment.

Benefits include : Excellent anti-wear, anti-corrosion, anti-rust performance, Low air retention/air entrainment, low foaming & good thermal stability and resistance to oxidation.

Confirms to DIN 51524, Part 2 (HLP).

Tech Sheet  
10318



25 Litre Drum

0026



25



162.70

ISO 46

### ATF Dexron II

ATF Dexron II is a high performance multi-application fluid. The high viscosity index & low pour point makes this product ideal for use in hydraulic systems & power steering. Conforms to GM Dexron II D & GM 6137-M.

Tech Sheet  
3148



25 Litre Drum

0026



25



213.75

ATF II

Due to restrictions imposed by the Transport of Dangerous Goods Act, this product is available for delivery to MAINLAND UK ONLY. For further information please contact our customer service department.