



## Spill Absorbents



Section 1 – Hydraulics

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep., Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE

### Oil Only Heavy Duty Pads



100 Pads Per Pack

0365		Absorbency Per Pack	£
<b>HDOP-100</b>	40cm x 50cm	108 Litre	<b>60.90</b>

### Oil Only Standard Dimple Pad



200 Pads Per Pack

0365		Absorbency Per Pack	£
<b>SOP-200</b>	40cm x 50cm	128 Litre	<b>86.00</b>


### Oil Only Folded Perforated Dimple Roll



18 Metre Rolls Per Pack

0365		Absorbency Per Pack		£
<b>FOR-3-18</b>	11cm x 18mtr	105 Litre	3	<b>110.50</b>
<b>FOR-1-18</b>	11cm x 18mtr	35 Litre	1	<b>35.77</b>


### General Purpose Standard Dimple Pad



200 Pads Per Pack

0365		Absorbency Per Pack	£
<b>SGP-200</b>	40cm x 50cm	128 Litre	<b>112.60</b>

### General Purpose Standard Perforated Dimple Roll



2 x 40 Metre Rolls Per Pack

0365		Absorbency Per Pack	£
<b>SGR-2-40</b>	40cm x 40mtr	153 Litre	<b>140.70</b>

### General Purpose Folded Perforated Dimple Roll



18 Metre Rolls Per Pack

0365		Absorbency Per Pack		£
<b>FGR-3-18</b>	11cm x 18mtr	105 Litre	3	<b>135.10</b>
<b>FGR-1-18</b>	11cm x 18mtr	35 Litre	1	<b>43.75</b>

### Oil Only Sock



12 Socks Per Pack

0365		Absorbency Per Pack	£
<b>SOS-12</b>	7.6cm x 120cm	51 Litre	<b>61.40</b>

### General Purpose Sock



12 Socks Per Pack

0365		Absorbency Per Pack	£
<b>SGS-12</b>	7.6cm x 120cm	35 Litre	<b>33.80</b>

### Reservoir Water Absorbent

Condensation occurs in all fuel & oil storage tanks & causes contamination in the form of water that settles on the bottom of the tank.

- Lower the water soaker into the tank, attach using the 3m cord (ensure it's sitting on the bottom of the tank).
- When it's fully absorbed any water, the nylon bladder expands into the mesh containment tube.
- Check monthly.
- Absorbs 269ml (TWA-44), 489ml (TWA-56) or 1.59L (TWA-100) of water.
- All 3 versions are 300mm long.



Netted

0225		£
<b>TWA-44</b>	44mm Diameter	<b>26.75</b>
<b>TWA-56</b>	56mm Diameter	<b>31.45</b>
<b>TWA-100</b>	100mm Diameter	<b>38.85</b>

Condensation occurs in all fuel & oil storage tanks & causes contamination in the form of water that settles on the bottom of the tank.

- Lower the tank dryer into the tank, attach using the 2.5m cord (ensure it's sitting on the bottom of the tank).
- Has a stainless steel rod/weight inside.
- When it's fully absorbed any water, the tank dryer swells.
- Check monthly.
- Absorbs 350ml of water.
- Ideal for use in vehicle & domestic storage tanks.
- 600mm long, diameter when full 40mm.



Standard

0225		£
<b>TD1</b>	40mm Diameter	<b>20.10</b>

### Loose Absorbents



16Kg Bag

0751	£
<b>CG16</b>	<b>18.00</b>