



Hydraulic Tooling

EAGLE PROPage Tech Sheet **10050**

General Purpose, Single Acting Cylinders

Features

- Use in confined spaces.
- Complies with ASME B30.1. High strength steel for durability and increased safety.
- Mounting holes permit easy fixing.
- Heavy-duty piston return spring.
- High quality EAB-201 quick couplers.
- Grooved piston end requires no saddle.
- Environmentally friendly painting process provides a durable anti-corrosion finish.

Lifetime Warranty

EAGLE PRO warrants all of its products to be free from defects in material and workmanship for the life of the product.

Damaged goods as a result of misuse or misapplication are not covered under this warranty.

All wearing parts are also excluded from this warranty.

EAGLE PRO products meet or exceed your performance requirements, however in the unlikely event that an EAGLE PRO product fails due to material or workmanship defect you may contact your supplier to have the issue investigated.

**5 Ton Capacity**

0346	↔ mm	↑ Min. Height mm	↑ Max. Height mm	£
ES-50	16	41	57	147.50
ES-51	25	110	136	206.00
ES-53	76	165	241	295.00
ES-55	127	216	343	340.70
ES-57	178	273	451	389.10
ES-59	232	324	556	551.85

10 Ton Capacity

0346	↔ mm	↑ Min. Height mm	↑ Max. Height mm	£
ES-101	25	90	115	190.75
ES-102	54	121	176	206.00
ES-104	105	171	276	234.00
ES-106	156	248	403	330.60
ES-108	203	298	502	381.50
ES-1010	257	349	607	462.90
ES-1012	305	400	705	561.95
ES-1014	356	451	806	793.50

15 Ton Capacity

0346	↔ mm	↑ Min. Height mm	↑ Max. Height mm	£
ES-151	25	124	149	457.70
ES-152	51	149	200	473.00
ES-154	102	200	302	595.10
ES-156	152	272	424	668.90
ES-158	203	322	526	739.95
ES-1510	254	373	627	831.60
ES-1512	305	424	729	1032.45
ES-1514	356	475	830	1134.25

25 Ton Capacity

0346	↔ mm	↑ Min. Height mm	↑ Max. Height mm	£
ES-251	25	140	165	478.10
ES-252	51	165	216	536.60
ES-254	102	216	318	618.00
ES-256	159	273	432	679.00
ES-258	210	324	533	846.85
ES-2510	260	375	635	973.95
ES-2512	311	425	736	1106.20
ES-2514	362	476	838	1289.35

30 Ton Capacity

0346	↔ mm	↑ Min. Height mm	↑ Max. Height mm	£
ES-308	210	387	597	1106.20

50 Ton Capacity

0346	↔ mm	↑ Min. Height mm	↑ Max. Height mm	£
ES-502	51	176	227	859.65
ES-504	102	227	329	941.00
ES-506	159	283	441	1134.25
ES-5013	337	461	797	2072.75

75 Ton Capacity

0346	↔ mm	↑ Min. Height mm	↑ Max. Height mm	£
ES-756	156	286	441	1775.10
ES-7513	334	492	826	3985.30

90 Ton Capacity

0346	↔ mm	↑ Min. Height mm	↑ Max. Height mm	£
ES-1006	168	357	526	2670.40
ES-10010	260	449	710	3687.60

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep, Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE

LIFETIME WARRANTY