



## Hydraulic Tooling



Page Tech Sheet **10067**

### Double Acting Cylinders

#### Features

- Complies with ASME B30.1. High strength steel for durability and increased safety.
- Double acting operation for fast piston retraction.
- Built-in safety valve prevents accidental over-pressurization.
- High quality EAB-201 quick couplers.
- Collar and piston threads for easy fixing.
- Environmentally friendly painting process provides a durable corrosion resistant finish.



#### 10 Ton Capacity

0346	↔ mm	↑ Min. Height mm	↑ Max. Height mm	£
ED-1010	254	409	663	737.50
ED-1012	305	457	762	925.75

#### 30 Ton Capacity

0346	↔ mm	↑ Min. Height mm	↑ Max. Height mm	£
ED-308	209	387	596	1531.00
ED-3014	368	546	914	2062.45

#### 50 Ton Capacity

0346	↔ mm	↑ Min. Height mm	↑ Max. Height mm	£
ED-506	156	331	487	1948.15
ED-5013	334	509	843	3438.35
ED-5020	511	733	1244	5816.20

#### 75 Ton Capacity

0346	↔ mm	↑ Min. Height mm	↑ Max. Height mm	£
ED-756	156	347	503	2710.95
ED-7513	333	525	858	4890.65

#### 95 Ton Capacity

0346	↔ mm	↑ Min. Height mm	↑ Max. Height mm	£
ED-1006	168	357	525	3252.75
ED-10013	333	524	857	4588.00
ED-10018	460	687	1147	8016.10

#### 145 Ton Capacity

0346	↔ mm	↑ Min. Height mm	↑ Max. Height mm	£
ED-1502	57	185	253	3341.70
ED-1506	156	385	541	6322.35
ED-15013	333	582	915	8756.25

#### 200 Ton Capacity

0346	↔ mm	↑ Min. Height mm	↑ Max. Height mm	£
ED-2006	152	430	582	10869.60
ED-20013	330	608	938	13216.95

#### 300 Ton Capacity

0346	↔ mm	↑ Min. Height mm	↑ Max. Height mm	£
ED-3006	153	485	638	14539.50

LIFETIME WARRANTY