



Hydraulic Tooling



Double Acting, High Tonnage Cylinder

Features

- Complies with ASME B30.1. High strength steel for durability and increased safety.
- Double acting operation for fast piston retraction.
- Built-in safety valve prevents accidental over-pressurization.
- High quality EAB-201 quick couplers.
- Collar and piston threads for easy fixing.
- Environmentally friendly painting process provides a durable corrosion resistant finish.

Tech Sheet 10068



50 Ton Capacity

0346	↔ mm	↑ Min. Height mm	↑ Max. Height mm	£
EDX-502	50	162	212	897.75
EDX-504	100	212	312	961.40
EDX-506	150	262	412	1070.60
EDX-508	200	312	512	1454.75
EDX-5010	250	362	612	1833.60
EDX-5012	300	412	712	2143.85

100 Ton Capacity

0346	↔ mm	↑ Min. Height mm	↑ Max. Height mm	£
EDX-1002	50	179	229	1197.90
EDX-1004	100	229	329	1658.10
EDX-1006	150	279	429	2863.60
EDX-1008	200	329	529	3565.65
EDX-10010	250	379	629	3903.90
EDX-10012	300	429	729	4125.15

150 Ton Capacity

0346	↔ mm	↑ Min. Height mm	↑ Max. Height mm	£
EDX-1502	50	196	246	2459.20
EDX-1504	100	246	346	3278.10
EDX-1506	150	296	446	4020.70
EDX-1508	200	346	546	4827.00
EDX-15010	250	396	646	5498.35
EDX-15012	300	446	746	6533.50

Pancake Locknut Cylinders

Features

- Extremely low height for use in confined spaces.
- Safety locknut for mechanical load holding.
- Tilting saddle.
- Complies with ASME B30.1. High strength steel for durability and increased safety.
- Overflow port functions as a stroke limiter.
- High flow EAB-201 quick coupler.
- Environmentally friendly painting process provides a durable corrosion resistant finish.

Tech Sheet 10069



Single Acting

0346	Capacity Tn	↔ mm	↑ Min. Height mm	↑ Max. Height mm	£
ELL-602	60	50	125	175	826.45
ELL-1002	100	50	137	187	1447.15
ELL-1602	160	45	148	193	2003.95
ELL-2002	200	45	155	200	2504.95
ELL-2502	260	45	159	204	3761.35
ELL-4002	400	45	178	223	7367.60
ELL-5002	520	45	192	237	9750.60

Single Acting, Locknut Cylinders

Features

- Safety locknut for mechanical load holding.
- High flow EAB-201 quick coupler.
- Overflow port functions as a stroke limiter.
- Environmentally friendly painting process provides a durable corrosion resistant finish.

Tech Sheet 10070



50 Ton Capacity

0346	↔ mm	↑ Min. Height mm	↑ Max. Height mm	£
EL-502	50	164	214	941.00
EL-504	100	214	313	1261.35
EL-506	150	264	413	1571.80
EL-508	200	313	513	2451.60
EL-5010	250	363	613	2845.90
EL-5012	300	413	713	3301.15

95 Ton Capacity

0346	↔ mm	↑ Min. Height mm	↑ Max. Height mm	£
EL-1002	50	187	236	1581.85
EL-1004	100	236	336	1859.15
EL-1006	150	287	436	2304.10
EL-1008	200	336	536	2769.45
EL-10010	250	386	636	3194.25
EL-10012	300	436	736	3743.65

140 Ton Capacity

0346	↔ mm	↑ Min. Height mm	↑ Max. Height mm	£
EL-1502	50	209	259	2337.30
EL-1504	100	259	358	3402.70
EL-1506	150	308	458	4020.70
EL-1508	200	358	558	4847.40
EL-15010	250	408	658	5483.10
EL-15012	300	458	758	6439.35