



Hydraulic Tooling

EAGLE PRO®

Ultra-High Pressure Hand Pump

Features

- Convenient high strength design, engineered for use in extreme environments.
- Dual speed pump.
- Built-in safety valve for overload protection.
- Unique handle designed to require less effort, saving you time and energy.

**Tech Sheet 10075****Two Stage**

0346	PSI	Oil Capacity cm ³	£
EPA-21621	20,000	1600	1335.10
EPA-31621	30,000	1600	1557.10
EPA-41621	40,000	1600	1773.95

Air Hydraulic Pumps

Features

- Can be used with a variety of hydraulic cylinders presses or other hydraulic tools.
- Operating air pressure between 0.6-1.0 PSI.
- Provides up to 10000 PSI of hydraulic pressure.
- Input port thread 1/4"-18 NPT and output 3/8"-18 NPT.
- Internal load limiting device avoids overload.
- Air exhaust muffler for quiet operation.
- Pumps feature both air and oil filters to reduce risk of damage from environmental contaminants.
- Various capacities available with plastic, aluminum, or steel housings.

**Tech Sheet 10076****Foot Operated, 680 bar**

0346	Oil Capacity cm ³	£
EPC-001	2294	572.25
EPC-002	1606	557.00
EPC-003	4506	610.40
EPC-004	7243	676.50
EPC-010	1606	554.35

**Tech Sheet 10076****Remote Control, 680 bar**

0346	Oil Capacity cm ³	£
EPC-008	1606	765.50
EPC-009	7243	1096.10

Electric Pumps

Features

- Covers most applications in the industry.
- High flow rate reaches 20in³/min and 39in³/min.
- 10ft 24V, remote control or solenoid control for operator safety.
- 0.75hp and 1.0 hp motor.
- Starts under full load.
- High strength frame with handle for maximum portability.

Please check Tech Data Sheet for further installation details**Tech Sheet 10077****Two Stage, 0.55 kW**

0346	Litres	For use with Cylinder	£
EPB-3B1P5A	0.95	Single Acting	2723.70
EPB-3B10P2A	2.4	Dump	2835.60
EPB-3B5P5A	5.9	Double Acting	2863.60

Two Stage, 0.75 kW

0346	Litres	Valve Type	For use with Cylinder	£
EPB-6B8P10A	11.8	Manual	Single Acting	4107.20
EPB-6B2D10A	11.8	Solenoid	Single Acting	6014.60
EPB-6B5P10A	11.8	Manual	Double Acting	4422.60
EPB-6B4P10A	11.8	Solenoid	Double Acting	7222.75

Features

- Covers most applications in the industry.
- High flow rate reaches 60in³/min and 120in³/min.
- 10ft 24V, remote control or solenoid control for operator safety.
- 2.0 hp and 3.0 hp motor.
- Starts under full load.
- High strength frame with handle for maximum portability.

Please check Tech Data Sheet for further installation details**Tech Sheet 10078****Two Stage, 1.5 kW, with Remote Control**

0346	Litres	Valve Type	For use with Cylinder	£
EPB-10B8P10A	11.8	Manual	Single Acting	4916.00
EPB-10B2D10A	11.8	Solenoid	Single Acting	6627.65
EPB-10B5P10A	11.8	Manual	Double Acting	4916.00
EPB-10B4D10A	11.8	Solenoid	Double Acting	7408.40

Two Stage, 2.24 kW, Manual Control

0346	Litres	For use with Cylinder	£
EPB-20B8M20C	24	Single Acting	5546.75
EPB-20B5M20C	24	Double Acting	5546.75

LIFETIME WARRANTY

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep., Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE