



# Hydraulic Tooling



Page Tech Sheet 10177

Section 1 – Hydraulics

## EHW Series Locking Ring

### EHWL-2 Series Reducer

0346	To Suit mm	£
H-32-2	32	16.80
H-36-2	36	18.65
H-41-2	41	22.20
H-46-2	46	25.10
H-50-2	50	30.75

### EHWL-4 Series Reducer

0346	To Suit mm	£
H-32-4	32	17.15
H-36-4	36	19.80
H-41-4	41	23.10
H-46-4	46	25.10
H-50-4	50	25.90
H-55-4	55	28.90
H-60-4	60	31.65
H-65-4	65	34.50

### EHWL-8 Series Reducer

0346	To Suit mm	£
H-55-8	55	27.95
H-60-8	60	31.65
H-65-8	65	33.60
H-70-8	70	37.30
H-75-8	75	41.00
H-80-8	80	42.50
H-85-8	85	53.15
H-90-8	90	55.90



### EHWL-14 Series Reducer

0346	To Suit mm	£
H-75-14	75	41.90
H-80-14	80	41.90
H-85-14	85	52.20
H-90-14	90	52.20
H-95-14	95	52.20
H-100-14	100	57.40
H-105-14	105	63.05
H-110-14	110	81.00
H-115-14	115	96.55

### EHWL-30 Series Reducer

0346	To Suit mm	£
H-90-30	90	53.70
H-95-30	95	61.55
H-100-30	100	68.00
H-105-30	105	76.60
H-110-30	110	95.05
H-115-30	115	115.20
H-120-30	120	125.65
H-130-30	130	146.55
H-145-30	145	176.20
H-155-30	155	190.55

## ESW Series Hydraulic Torque Wrench

### Features

- Accuracy within  $\pm 3\%$
- 8 models with a range from 189 to 48670 Nm
- Covers the majority of bolt sizes
- Square drive operation
- 360° adjustable reaction arm
- Heat treated
- Lifetime warranty



Maximum Working Pressure: 700 bar

### Square Drive

0346	Square Drive	To Suit mm	Torque Nm	kg	£
ESW-1	3/4"	24-55	189-1897	2	3292.25
ESW-3	1"	30-75	450-4510	4	4122.70
ESW-5	1.1/2"	36-130	737-7368	7	5650.25
ESW-8	1.1/2"	36-130	1078-10784	9.1	6592.00
ESW-10	1.1/2"	36-130	1550-15503	13.1	7533.70
ESW-20	2.1/2"	55-165	2666-26658	25	9417.15
ESW-25	2.1/2"	55-165	3472-34724	31	10779.10
ESW-35	2.1/2"	55-165	4867-48670	45	12971.60

