



ISO B Interchange Couplings & Plugs



Tech Sheet 10003

ISO B Interchange



Brass ISO B Coupling with Nitrile Seal, BSPP

0249			
HKS02B	1/8"	200	25.95
HKS04B	1/4"	180	25.95
HKS06B	3/8"	180	36.00
HKS08B	1/2"	160	57.30
HKS12B	3/4"	120	96.85
HKS16B	1"	120	143.40

Brass ISO B Coupling with Viton Seals, BSPP

0249			
HKS02B-V	1/8"	200	26.80
HKS04B-V	1/4"	180	26.80
HKS06B-V	3/8"	180	37.10
HKS08B-V	1/2"	160	59.15
HKS12B-V	3/4"	120	99.95
HKS16B-V	1"	120	150.30



Brass ISO B Plug with Nitrile Seal, BSPP

0249			
HKP02B	1/8"	200	8.25
HKP04B	1/4"	180	9.40
HKP06B	3/8"	180	12.75
HKP08B	1/2"	160	20.30
HKP12B	3/4"	120	32.60
HKP16B	1"	120	54.50

Brass ISO B Plug with Viton Seals, BSPP

0249			
HKP02B-V	1/8"	200	11.60
HKP04B-V	1/4"	180	11.60
HKP06B-V	3/8"	180	13.20
HKP08B-V	1/2"	160	20.95
HKP12B-V	3/4"	120	33.60
HKP16B-V	1"	120	56.20



ISO B Plug & Coupling Dust Protection Cap

8111		
ISOBDP-4	1/4"	1.65
ISOBDP-6	3/8"	2.10
ISOBDP-8	1/2"	2.80
ISOBDP-12	3/4"	3.95
ISOBDP-16	1"	4.90

Section 2 – Hydraulic QRC

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep., Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE

ISO Trailer Brake, Interchange Couplings & Plugs



Tech Sheet 2126

Used to connect the hydraulic braking system of tractors to their trailers.

Temperature Range: -25°C to +120°C Nitrile

Maximum Working Pressure: 220 bar

High Pressure Screw-On Coupling (Carbon Steel), 65 Series, ISO 5676



Socket with Nitrile Seals, BSPP & Metric

8111		
HFSFC6538	3/8"	21.40
HFSFC6512	1/2"	25.65
HFSFC6518	M18 x 1.5	23.20
HFSFC6522	M22 x 1.5	23.20



Plug with Nitrile Seals, BSPP & Metric

8111		
HFSFP6538	3/8"	11.85
HFSFP6512	1/2"	12.90
HFSFP6518	M18 x 1.5	13.10
HFSFP6522	M22 x 1.5	12.90