



ISO 16028 Interchange, Flat Face Couplings



Tech Sheet 10233

Section 2 – Hydraulic QRC

ISO 16028 Interchange

Designed to meet or exceed the requirements of ISO 16028. Flush face & dry break design facilitates easy cleaning prior to connection. Manufactured from high strength steel construction.

Other seals available on request

Temperature Range:
-25°C to +120°C Nitrile
-25°C to +175°C Viton



Steel Flat Face Couplings with Nitrile Seals, BSPP

8111	Body	bar	£
HKSFF04CS	1/4" 1/4"	315	24.40
HKSFF06CS	3/8" 3/8"	250	32.20
HKSFF0608CS	1/2" 3/8"	250	33.60
HKSFF08CS	1/2" 1/2"	250	48.35
HKSFF12CS	3/4" 1/2"	250	60.05
HKSFF1212CS	3/4" 3/4"	250	57.25
HKSFF16CS	1" 3/4"	250	76.40
HKSFF1616CS	1" 1"	200	90.65
HKSFF2016CS	1.1/4" 1"	200	135.10



Steel Flat Face Plugs with Nitrile Seals, BSPP

8111	Body	bar	£
HKPFF04CS	1/4" 1/4"	350	10.50
HKPFF06CS	3/8" 3/8"	350	13.70
HKPFF0608CS	1/2" 3/8"	350	15.45
HKPFF08CS	1/2" 1/2"	300	20.55
HKPFF12CS	3/4" 1/2"	300	29.15
HKPFF1212CS	3/4" 3/4"	300	31.05
HKPFF16CS	1" 3/4"	300	38.50
HKPFF1616CS	1" 1"	210	48.85
HKPFF2016CS	1.1/4" 1"	210	57.90

Dust Protection Cap, Plug



8111	To Suit	£
FFDP-04	1/4"	1.60
FFDP-06	3/8"	1.90
FFDP-08	1/2"	2.80
FFDP-12	3/4"	4.25
FFDP-16	1"	5.95

Dust Protection Cap, Coupling



8111	To Suit	£
FFDC-04	1/4"	1.60
FFDC-06	3/8"	1.90
FFDC-08	1/2"	2.80
FFDC-12	3/4"	4.25
FFDC-16	1"	5.95

For Breaker Hose Assemblies see page 58



- Hydraulics
- Hydraulic QRC
- Pneumatic QRC
- Ind. Air Prep., Monitor & Test
- KELM™ Pneumatics
- Pneumatic & Vacuum Equipment
- Valves
- Ring Main Systems
- Adaptors & Fittings
- Stainless Steel
- Malleable Iron
- Hose, Tubing & Couplings
- Clamps & Clips
- Sprays & Adhesives
- Blow Guns & Vacuum
- Wash Down & Fuelling
- Air Tools
- Tools, Hardware & PPE