



## Hydraulic Couplings



Only plug and socket with same thread fit together.

Ideal for hydraulic dump trucks, oil field equipment, spreading equipment and applications requiring the ability to connect or disconnect under pressure. With Standard Seals: Buna-N (Nitrile).

Temperature Range: -25°C to +120°C

### Tech Sheet 2127

#### Screw-On Couplings, 97 Series

Steel Body/Zinc Plated Steel Wing Nut.



Wing Nut, NPTF

8111			£
HFSFC9710	1"	230	44.95



Plug, NPTF

8111			£
HFSFP9710	1"	230	26.35

### Tech Sheet 2128

#### Screw-On Couplings, 98 Series

Brass Body/Zinc Plated Steel Wing Nut.



Wing Nut, NPTF

8111			£
HFBFC9834	3/4"	210	60.75
HFBFC9810	1"	210	77.35
HFBFC98114	1.1/4"	190	136.35
HFBFC98112	1.1/2"	175	147.45

Plug, NPTF



8111			£
HFBFP9834	3/4"	210	44.40
HFBFP9810	1"	210	49.45
HFBFP98114	1.1/4"	190	101.35
HFBFP98112	1.1/2"	175	123.40

## High Pressure Spin-on Couplings (Carbon Steel)



### Tech Sheet 10005

#### 88 Series

**Interchangeability:**  
Hansen HP3 Series  
Parker 3000 Series  
Faster PVVM Series

DNP PVS Series  
Stucchi IVHP Series  
Safeway S30 Series

This series of couplings with their threaded union locking system and precision ball-type check valves, are designed for extreme high pressure applications such as found on portable hydraulic rams.

Temperature Range: -25°C to +120°C  
Maximum Working Pressure: 700 bar

Coupling with Nitrile Seals, NPTF

8111			£
HFSFC8814	1/4"	21.90	
HFSFC8838	3/8"	22.05	



Plug with Nitrile Seals, NPT

8111			£
HFSFP8814	1/4"	13.30	
HFSFP8838	3/8"	13.60	



88 Series Aluminium Dust Covers

8111	To Suit	£
HFSFC-14-DP	1/4"	5.05
HFSFC-38-DP	3/8"	5.25
HFSFP-14-DC	1/4"	6.40
HFSFP-38-DC	3/8"	7.10