



## Hydraulic Couplings

Section 2 – Hydraulic QRC

### Flat Face HQ Series Couplings

Tech Sheet **10016**

The 3/8" size conforms in all aspects to the HTMA standard.  
(HTMA: Hydraulic Tool Manufacturers Association)



**Maximum Working Pressure:**  
Safety Factor = 1:4

**For Static Pressure:**  
Safety Factor = 1:2



Female Thread, BSPP

	0223		Body		£
FF10-04		1/4"	1/4"	400	50.60
FF38F		3/8"	3/8"	375	42.60
FF38-12F		1/2"	3/8"	375	44.45
FF20-08		1/2"	1/2"	350	82.95
FF10-12		3/4"	1/2"	350	80.00
FF20-12		3/4"	3/4"	350	151.00
FF10-16		1"	1"	350	217.40
FF10-20		1.1/4"	1.1/4"	350	309.20

### Flat Face HQ Series Plugs



**Maximum Working Pressure:**  
Safety Factor = 1:4

**For Static Pressure:**  
Safety Factor = 1:2



Female Thread, BSPP

	0223		Body		£
FM10-04		1/4"	1/4"	400	25.55
FF38M		3/8"	3/8"	375	26.45
FF38-12M		1/2"	3/8"	375	29.10
FM20-08		1/2"	1/2"	350	56.90
FM10-12		3/4"	1/2"	350	53.50
FM20-12		3/4"	3/4"	350	109.90
FM10-16		1"	1"	350	111.00
FM10-20		1.1/4"	1.1/4"	350	199.95

### Dust Caps

Tech Sheet **815**



For Plugs

	0223	To Suit	£
FF14P		FM10-04	3.50
FP3DC		FF38M	3.80
FF3812P		FF38-12M	4.30
FF12P		FM20-08	4.30
FF34P		FM20-12	9.50
FF1P		FM10-16	7.10
FF114P		FM10-20	8.35



For Couplings

	0223	To Suit	£
FF14C		FF10-04	3.50
FP3DP		FF38F & FF38-12F	3.80
FF12C		FF20-08	4.50
FF34C		FF20-12	5.65
FF1C		FF10-16	7.10
FF114C		FF10-20	8.35

A full range of dust caps and plugs are available to suit all flat face couplings. Contact our Sales Office for details.

For Breaker Hose  
**Assemblies**  
see page 58

