



Series AP97



Temperature Range:
-40°C to +120°C
Standard Seal NBR

Maximum Static Working Pressure:
PB 19 bar (300 PSI)



Interchangeability:
Standard Schrader Series

Application:
General Purpose Pneumatic Coupling

Material:
Coupler Body: Zinc & Brass
Key Part: Zinc Alloy
Sleeve: Zinc Plated Steel
Springs: AISI 301
Locking O-Ring: AISI 301
Seals: Buna-N (Nitrile)



Actual Size

Series AP97 Couplings



Male Thread, BSPT

0097		
AP97-14M	1/4"	13.95
AP97-38M	3/8"	13.95



Female Thread, BSPT


0097		
AP97-14F	1/4"	13.95

Plugs



Male Thread, BSPT

1710				
17SFAK10SXN	1/8"	11	37	4.65
17SFAK13SXN	1/4"	14	42	3.50
17SFAK17SXN	3/8"	17	42	3.65
17SFAK21SXN	1/2"	21	43	3.75



Female Thread, BSPP

1710				
17SFIW10SXN	1/8"	14	33	4.20
17SFIW13SXN	1/4"	17	36	3.50
17SFIW17SXN	3/8"	19	39	3.65
17SFIW21SXN	1/2"	24	41	4.80



Hose Tail

1710			
17SFTF06SXN	6mm (1/4")	58	3.50
17SFTF08SXN	8mm (5/16")	52	3.50
17SFTF10SXN	10mm (3/8")	52	3.50
17SFTF13SXN	13mm (1/2")	52	5.55

For **KELM™ One Touch+**
Plastic Push-in Fittings
(16 bar rated)
see pages 535-539

