



Series 02KA Micro-Coupler



Page Tech Sheet **10276**



Temperature Range:
-20°C to +100°C
Standard Seal NBR



Maximum Static Working Pressure:
PB 35 bar (500 PSI)



Single Shut Off



Actual Size

Material:

Brass and Buna Seal (Standard Series) Coupling and Plug

Application:

Medical and Dental Equipment, Robotics Instrumentation, Air Brush Systems and Pneumatic Systems

Couplings



Male Thread

2010				
02KAAM03MPX	M3	6	19	54.95



Hose Tail

2010				
02KATF02MPX	2	6	21	31.30

Plugs



Male Thread

2010				
02SFAM03MXX	M3	6	11	8.05



Female Thread

2010				
02SFIM03MXX	M3	6	10	8.05



Hose Tail

2010			
02SFTF03MXX	3	13	13.85

For **KELM™** Micro One Touch Plastic Push-In Fittings see pages 547-552



Other materials, seals and finishes available on request, please contact our technical department for further details.

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep, Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE