



Series 13KA

Page Tech Sheet **501**



Temperature Range:
-20°C to +100°C
Standard Seal NBR



Maximum Static Working Pressure:
PB 35 bar (500 PSI)



Single Shut Off

Interchangeability:

Rectus 03, Nitto Kohki 200 (Japan)
Cejn 314, 315

Material:

Brass and Buna Seal (Standard Series)
Coupling

Application:

General Purpose Pneumatic Coupling



Actual Size

Section 3 – Pneumatic QRC

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep, Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE

Couplings




Male Thread, BSPT

1310				£
13KAAK13MPX	1/4"	22	49	13.00
13KAAK17MPX	3/8"	22	49	24.65
13KAAK21MPX	1/2"	22	53	14.65



Female Thread, BSPP

1310				£
13KAIW13MPX	1/4"	22	45	13.00
13KAIW17MPX	3/8"	22	45	13.00
13KAIW21MPX	1/2"	24	48	14.65



Hose Tail

1310	To Suit Hose I.D.			£
13KATF06MPX	6mm (1/4")	21	62	14.05
13KATF08MPX	8mm (5/16")	21	62	14.05
13KATF10MPX	10mm (3/8")	21	62	27.45
13KATF13MPX	13mm (1/2")	21	62	15.00

Plugs



Male Thread, BSPT

1310				£
13SFAK13SXN	1/4"	14	37	5.20
13SFAK17SXN	3/8"	17	37	5.20
13SFAK21SXN	1/2"	22	44	10.25



Female Thread, BSPP

1310				£
13SFIW13SXN	1/4"	17	33	5.20
13SFIW17SXN	3/8"	19	33	5.20
13SFIW21SXN	1/2"	24	36	10.25



Hose Tail

1310	To Suit Hose I.D.		£
13SFTF06SXN	6mm (1/4")	48	4.70
13SFTF08SXN	8mm (5/16")	48	4.70
13SFTF10SXN	10mm (3/8")	48	4.80
13SFTF13SXN	13mm (1/2")	48	6.10

Other materials, seals and finishes available on request, please contact our technical department for further details.