



Series 14KA



Page Tech Sheet 502



Temperature Range:
-20°C to +100°C
Standard Seal NBR



Maximum Static Working Pressure:
PB 35 bar (500 PSI)



Single Shut Off

Interchangeability:

Rectus 22, ARO 210, Parker 50,
Cejn 300, JWL 522, JWL 532

Material:

Brass and Buna Seal
(Standard Series) Coupling

Application:

General Purpose Pneumatic Coupling



Actual Size

Section 3 – Pneumatic QRC

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep, Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE

Couplings



Male Thread, BSPP

0194				
14KAAW13MPX	1/4"	22	43	8.90
14KAAW17MPX	3/8"	22	43	8.90
14KAAW21MPX	1/2"	22	46	9.40



Female Thread, BSPP

0194				
14KAIW13MPX	1/4"	22	43	8.90
14KAIW17MPX	3/8"	22	43	9.50
14KAIW21MPX	1/2"	24	46	9.65



Hose Tail

0194				
14KATF06MPX	6	21	60	9.75
14KATF08MPX	8	21	60	9.75
14KATF10MPX	10	21	60	9.75
14KATF13MPX	13	21	60	9.75

Plugs



Male Thread, BSPT

0194				
14SFAK13SXN	1/4"	14	41	1.70
14SFAK17SXN	3/8"	17	41	3.00
14SFAK21SXN	1/2"	22	46	4.20



Female Thread, BSPP

0194				
14SFIW13SXN	1/4"	17	35	1.70
14SFIW17SXN	3/8"	19	35	3.00
14SFIW21SXN	1/2"	24	39	4.20



Hose Tail

0194			
14SFTF06SXN	6	49	3.00
14SFTF08SXN	8	49	3.40
14SFTF10SXN	10	49	4.20

Other materials, seals and finishes available on request, please contact our technical department for further details.