



Series 17KA & Accessories

Page Tech Sheet 503

Section 3 - Pneumatic QRC

Temperature Range:
-20°C to +100°C
Standard Seal NBR

Maximum Static Working Pressure:
PB 35 bar (500 PSI)



Interchangeability:
Standard Schrader Series NW5
Flow Rate:
865 L/Min

Material:
Steel Nickel Plated, Buna Seal (Standard Series Coupling)
Application:
General Purpose Pneumatic Coupling, Garages, Workshops

Couplings



Male Thread, BSPT

1710				£
17KAAK13SPN	1/4"	19	63	17.20
17KAAK17SPN	3/8"	19	62	17.20
17KAAK21SPN	1/2"	22	63	20.50

Plugs



Male Thread, BSPT

1710				£
17SFAK10SXN	1/8"	11	37	4.65
17SFAK13SXN	1/4"	14	42	3.50
17SFAK17SXN	3/8"	17	42	3.65
17SFAK21SXN	1/2"	21	43	3.75



Actual Size

Female Thread, BSPP



1710				£
17KAIW13SPN	1/4"	19	58	16.65
17KAIW17SPN	3/8"	19	57	18.05
17KAIW21SPN	1/2"	24	60	20.50

Female Thread, BSPP



1710				£
17SFIW10SXN	1/8"	14	33	4.20
17SFIW13SXN	1/4"	17	36	3.50
17SFIW17SXN	3/8"	19	39	3.65
17SFIW21SXN	1/2"	24	41	4.80

Y Connector

2 x Coupling Outlets, 1 x Plug Inlet



1710		£
17Y	114	40.20

Triple Outlet Connectors

3 x Coupling Outlets, 1 x 3/8" BSPP Inlet



1710		£
17W	111	64.50

Hose Tail



1710	To Suit Hose I.D.			£
17KATF06SPN	6mm (1/4")	19	76	21.00
17KATF08SPN	8mm (5/16")	19	76	21.00
17KATF10SPN	10mm (3/8")	19	76	21.00
17KATF13SPN	13mm (1/2")	19	76	21.00

Hose Tail



1710	To Suit Hose I.D.		£
17SFTF06SXN	6mm (1/4")	58	3.50
17SFTF08SXN	8mm (5/16")	52	3.50
17SFTF10SXN	10mm (3/8")	52	3.50
17SFTF13SXN	13mm (1/2")	52	5.55

Leader Hoses



A 'Leader Hose' is a length of flexible hose which should be fitted between an air tool & the connecting coupling.

By absorbing the impact of a pneumatic impact tool, a leader hose will significantly increase the life expectancy of the coupling.

3/8" Bore Rubber-Tech Hose, Plug One End, Thread One End, BSPT Male

1710			£
LH17/13K	1/4"	381	7.85
LH17/17K	3/8"	381	8.55
LH17/21K	1/2"	381	9.40

WARNING - Leader Hoses



The Health & Safety Executive guide states - "the plug should not be screwed directly into the inlet port, but should be fitted onto a short isolation hose, thus isolating the plug & coupling from the tool vibration".

Other materials, seals and finishes available on request, please contact our technical department for further details.