



Series 18KA



Temperature: Range:
-20°C to +100°C
Standard Seal NBR

Maximum Static Working Pressure:
PB 35 bar (500 PSI)



Interchangeability:
ISO 6150 C, Staubli RBE06, Cejn 291

Material:
Brass Nickel Plated, Buna Seal (Standard Series Coupling)
Application:
Industrial Pneumatic Coupling, Robust Design

Couplings



Male Thread, BSPT

0194				£
18KAAK13MPN	1/4"	19	63	33.25
18KAAK17MPN	3/8"	19	62	33.25
18KAAK21MPN	1/2"	22	63	34.10



Female Thread, BSPP

0194				£
18KAIW13MPN	1/4"	19	58	33.25
18KAIW17MPN	3/8"	19	57	33.25
18KAIW21MPN	1/2"	24	60	34.10



Plastic Hose Connection

0194	To Fit Tube Size mm			£
18KAKO08MPN	6 x 8	19	63	36.20
18KAKO10MPN	8 x 10	19	67	36.60
18KAKO12MPN	9 x 12	19	67	37.10



Hose Tail

0194	To Suit Hose I.D. mm			£
18KATF06MPN	6	19	76	33.25
18KATF08MPN	8	19	76	33.25
18KATF09MPN	9	19	76	33.25
18KATF10MPN	10	19	76	33.25
18KATF13MPN	13	19	76	33.25



Actual Size



Plastic Hose Connection with Spring Guard

0194	To Fit Tube Size mm			£
18KAKK08MPN	6 x 8	19	155	42.55
18KAKK10MPN	8 x 10	19	165	42.85

Plugs



Male Thread, BSPT

0194			£
18SFAK13SXN	1/4"	41	10.75
18SFAK17SXN	3/8"	41	28.00



Female Thread, BSPP

0194				£
18SFIW13SXN	1/4"	19	43	6.70
18SFIW17SXN	3/8"	19	44	7.20



Hose Tail

0194	To Suit Hose I.D. mm		£
18SFTF06SXN	6	56	6.40
18SFTF08SXN	8	56	6.40
18SFTF10SXN	10	56	6.55

Other materials, seals and finishes available on request, please contact our technical department for further details.

- Hydraulics
- Hydraulic QRC
- Pneumatic QRC
- Ind. Air Prep, Monitor & Test
- KELM™ Pneumatics
- Pneumatic & Vacuum Equipment
- Valves
- Ring Main Systems
- Adaptors & Fittings
- Stainless Steel
- Malleable Iron
- Hose, Tubing & Couplings
- Clamps & Clips
- Sprays & Adhesives
- Blow Guns & Vacuum
- Wash Down & Fuelling
- Air Tools
- Tools, Hardware & PPE