



Series 18KE Self Venting



Page Tech Sheet **504**



Temperature Range:
-20°C to +60°C
Standard Seal NBR



Maximum Static Working Pressure:
PB 8 bar (116 PSI)



Single Shut Off

Material:

Brass Nickel Plated, Buna Seal
(Standard Series Coupling)

Application:

General Purpose Pneumatic Coupling,
Self-Venting on Disconnection

Couplings



Male Thread, BSPT

0194				
18KEAK13SPN	1/4"	24	67	53.80
18KEAK17SPN	3/8"	24	67	52.20
18KEAK21SPN	1/2"	24	67	53.80



Female Thread, BSPP

0194				
18KEIW13SPN	1/4"	24	63	53.80
18KEIW17SPN	3/8"	24	60	52.20
18KEIW21SPN	1/2"	24	65	53.80



Actual Size

Section 3 – Pneumatic QRC

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep, Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE



Hose Tail

0194	To Suit Hose I.D. mm			
18KETF06SXN	6	24	81	53.80
18KETF10SXN	10	24	81	53.80

Safety Coupling



Hose Tail

0194	To Suit Hose I.D. mm			
18KETF06SPN	6	24	81	58.10
18KETF08SPN	8	24	81	58.10
18KETF09SPN	9	24	81	58.10
18KETF10SPN	10	24	81	58.10
18KETF13SPN	13	24	81	58.10

Plugs



Male Thread, BSPT

0194			
18SFAK13SXN	1/4"	41	10.75
18SFAK17SXN	3/8"	41	28.00



Female Thread, BSPP

0194			
18SFIW13SXN	1/4"	19	6.70
18SFIW17SXN	3/8"	19	7.20



Hose Tail

0194	To Suit Hose I.D. mm		
18SFTF06SXN	6	56	6.40
18SFTF08SXN	8	56	6.40
18SFTF10SXN	10	56	6.55

Other materials, seals and finishes available on request, please contact our technical department for further details.