



Series 19KA & Accessories



Page Tech Sheet **505**



Temperature Range:
-20°C to +100°C
Standard Seal NBR



Maximum Static Working Pressure:
PB 35 bar (500 PSI)



Single Shut Off

Interchangeability:
Standard PCL Series

Material:
Steel Nickel Plated, Buna Seal
(Standard Series Coupling)

Application:
General Purpose Pneumatic Coupling,
Original PCL



Actual Size

Section 3 – Pneumatic QRC

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep, Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE

Couplings



Male Thread, BSPT

1910	mm	L mm	£	
19KAAK13MPX	1/4"	19	63	12.70
19KAAK17MPX	3/8"	19	63	19.60
19KAAK21MPX	1/2"	22	68	19.60



Female Thread, BSPP

1910	mm	L mm	£	
19KAIW13MPX	1/4"	19	58	17.10
19KAIW17MPX	3/8"	19	58	19.60
19KAIW21MPX	1/2"	24	60	19.60



Hose Tail

1910	To Suit Hose I.D.	mm	L mm	£
19KATF06MPX	6mm (1/4")	19	76	20.40
19KATF08MPX	8mm (5/16")	19	76	15.70
19KATF10MPX	10mm (3/8")	19	76	15.70
19KATF13MPX	13mm (1/2")	19	76	15.70

Plugs



Male Thread, BSPT

1910	mm	L mm	£	
19SFAK13SXN	1/4"	14	50	2.15
19SFAK17SXN	3/8"	17	50	3.10
19SFAK21SXN	1/2"	21	57	4.40



Female Thread, BSPP

1910	mm	L mm	£	
19SFIW13SXN	1/4"	17	46	3.10
19SFIW17SXN	3/8"	17	47	5.20
19SFIW21SXN	1/2"	19	47	5.10



Hose Tail

1910	To Suit Hose I.D.	L mm	£
19SFTF05SXN	5mm	60	2.15
19SFTF06SXN	6mm (1/4")	60	2.15
19SFTF08SXN	8mm (5/16")	60	2.15
19SFTF10SXN	10mm (3/8")	60	3.20
19SFTF13SXN	13mm (1/2")	60	4.55

Other materials, seals and finishes available on request, please contact our technical department for further details.