



Series 20KB

Page Tech Sheet **507**



Temperature Range:
-20°C to +100°C
Standard Seal NBR



Maximum Static Working Pressure:
PB 35 bar (500 PSI)



Double Shut Off



Actual Size

Material:

Brass, Buna Seal
(Standard Series Coupling)

Application:

General Purpose Pneumatic Coupling, Medical, Dental, Robotics, Instrumentation

Section 3 – Pneumatic QRC

Couplings



Male Thread, BSPP

2010				
20KBAM05MPX	M5	9	26	23.25
20KBAM10MPX	1/8"	11	28	23.25



Female Thread, BSPP

2010				
20KBIM05MPX	M5	9	26	23.25
20KBIM10MPX	1/8"	12	28	23.25



Plastic Tube Connection

2010				
20KBKO04MPX	3 x 4	9	34	24.05
20KBKO05MPX	3 x 5	9	34	24.05
20KBKO06MPX	4 x 6	9	34	24.05



Hose Tail

2010				
20KBTF03MPX	3	11	35	24.05
20KBTF04MPX	4	11	35	24.05

Plugs



Male Thread, BSPP

2010				
20SBAM05MPX	M5	9	28	18.55
20SBAM10MPX	1/8"	11	30	19.70



Female Thread, BSPP

2010				
20SBIM05MPX	M5	9	26	18.55
20SBIM10MPX	1/8"	12	30	19.70



Plastic Tube Connection

2010				
20SBKO04MPX	3 x 4	9	30.5	21.50
20SBKO06MPX	4 x 6	9	30.5	23.70



Hose Tail

2010				
20SBTF03MPX	3	8	36	20.30
20SBTF04MPX	4	8	36	20.30

Other materials, seals and finishes available on request, please contact our technical department for further details.