



Series 21KA Push-in



Page Tech Sheet **508**



Temperature Range:
-20°C to +100°C
Standard Seal NBR



Maximum Static Working Pressure:
PB 35 bar (500 PSI)



Single Shut Off

Flow Rate:

6mm 450 L/Min @ 1 bar
8mm 700 L/Min @ 1 bar

Material:

Brass Nickel Plated, Buna Seal (Standard Series Coupling)

Application:

Usable for Air, Oil and Water. Ideally suited where Tubing is often changed



Actual Size

Couplings



Push-in

2010	OD mm	mm	L mm	£
21KARP06MPN	6	14	43.5	25.00
21KARP08MPN	8	17	48	19.50

Plugs



Push-in

2010	OD mm	mm	L mm	£
21SFRP06MPN	6	17	30.5	9.85
21SFRP08MPN	8	17	37	15.20

For **KELM™** Pneumatic Tube
see pages 573-576

Other materials, seals and finishes available on request, please contact our technical department for further details.

Section 3 – Pneumatic QRC

- Hydraulics
- Hydraulic QRC
- Pneumatic QRC**
- Ind. Air Prep, Monitor & Test
- KELM™ Pneumatics
- Pneumatic & Vacuum Equipment
- Valves
- Ring Main Systems
- Adaptors & Fittings
- Stainless Steel
- Malleable Iron
- Hose, Tubing & Couplings
- Clamps & Clips
- Sprays & Adhesives
- Blow Guns & Vacuum
- Wash Down & Fuelling
- Air Tools
- Tools, Hardware & PPE