



Series 21KB




Page Tech Sheet **509**



Temperature Range:
-20°C to +100°C
Standard Seal NBR



Maximum Static Working Pressure:
PB 35 bar (500 PSI)



Double Shut Off



Actual Size

Flow Rate:
560 L/Min

Material:
Brass, Buna Seal (Standard Series Coupling)

Application:
General Purpose Pneumatic Coupling, Medical, Dental, Robotics, Instrumentation

Section 3 – Pneumatic QRC

Couplings



Male Thread, BSPP

2110				£
21KBAW10MPX	1/8"	14	36	19.70
21KBAW13MPX	1/4"	17	38	19.70



Female Thread, BSPP

2110				£
21KBIW10MPX	1/8"	14	36	19.70
21KBIW13MPX	1/4"	17	38	19.70



Plastic Hose Connection

2110				£
21KCKO06MPX	6 x 4	14	42	23.25
21KCKO08MPX	8 x 6	14	42	23.25



Hose Tail

2110				£
21KBTFO4MPX	4mm (1/8")	14	46	21.50
21KBTFO6MPX	6mm (1/4")	14	46	21.50
21KBTFO8MPX	8mm (5/16")	14	46	21.95

Plugs



Male Thread, BSPP

2110				£
21SBAW10MPX	1/8"	14	40	15.10
21SBAW13MPX	1/4"	17	42	15.40



Female Thread, BSPP

2110				£
21SBIW10MPX	1/8"	14	40	15.10
21SBIW13MPX	1/4"	17	42	15.40



Hose Tail

2110				£
21SBTF06MPX	6mm (1/4")	14	50	19.00
21SBTF08MPX	8mm (5/16")	14	50	19.70



Plastic Hose Connection

2110				£
21SBKO06MPX	6 x 4	14	46	19.60
21SBKO08MPX	8 x 6	14	46	19.60

Other materials, seals and finishes available on request, please contact our technical department for further details.