



## Series 21KS Safety Lock



Page Tech Sheet **10279**



**Temperature Range:**  
-20°C to +100°C  
Standard Seal NBR



**Maximum Static Working Pressure:**  
PB 35 bar (500 PSI)



Single Shut Off



Actual Size

**Interchangeability:**  
Rectus Design

**Material:**  
Brass Nickel Plated, Buna Seal  
(Standard Series Coupling)

**Application:**  
Air Breathing Systems, Medical, Laboratories,  
Diving Suits etc.

### Couplings




Male Thread, BSPP

2110				£
21KSAW10MPN	1/8"	14	36	28.40
21KSAW13MPN	1/4"	17	38	28.40



Female Thread, BSPP

2110				£
21KSIW10MPN	1/8"	14	36	28.40
21KSIW13MPN	1/4"	17	38	28.40



Hose Tail

2110	To Suit Hose I.D.			£
21KSTF06MPN	6mm (1/4")	14	46	30.35
21KSTF08MPN	8mm (5/16")	14	46	31.15
21KSTF10MPN	10mm (3/8")	14	46	31.50

### Plugs




Male Thread, BSPP

2110				£
21SSAW10MXN	1/8"	14	25	12.30
21SSAW13MXN	1/4"	17	28	12.45



Female Thread, BSPP

2110				£
21SSIW10MXN	1/8"	14	25	12.30
21SSIW13MXN	1/4"	17	26	12.45



Hose Tail

2110	To Suit Hose I.D.			£
21SSTF06MXN	6mm (1/4")		32	10.80
21SSTF08MXN	8mm (5/16")		32	11.05
21SSTF10MXN	10mm (3/8")		33	11.40

Other materials, seals and finishes available on request, please contact our technical department for further details.

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep., Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE