



## Series 21 Thermoplastic



Page Tech Sheet **10280**

**Temperature Range:**

Rectupom -20°C to +80°C  
Rectuchem -20°C to +120°C

**Working Pressure:**

Rectupom 10 bar @ 20°C  
Rectuchem 8 bar @ 20°C



Single Shut Off



Double Shut Off



Actual Size

**Interchangeability:**

Rectus Design

**Material:**

Rectupom – Delrin-Acetal  
Rectuchem – PVDF

**Application:**

Suitable for Liquids, Gases, Drinking Water,  
Laboratories, Medical Technology and Food Areas

### Couplings



Male Thread, BSPP, RectuPom

| 2110               |      |    |    | £            |
|--------------------|------|----|----|--------------|
| <b>21KBAW10DPX</b> | 1/8" | 17 | 50 | <b>16.35</b> |
| <b>21KBAW13DPX</b> | 1/4" | 17 | 52 | <b>16.45</b> |



Female Thread, BSPP, RectuPom

| 2110               |      |    |    | £            |
|--------------------|------|----|----|--------------|
| <b>21KBIW10DPX</b> | 1/8" | 17 | 53 | <b>16.75</b> |
| <b>21KBIW13DPX</b> | 1/4" | 17 | 53 | <b>16.35</b> |



Hose Tail, RectuPom

| 2110               | To Suit Hose I.D. mm |    |    | £            |
|--------------------|----------------------|----|----|--------------|
| <b>21KBTf04DPX</b> | 4                    | 17 | 60 | <b>21.80</b> |
| <b>21KBTf06DPX</b> | 6                    | 17 | 60 | <b>23.35</b> |



Quick Fit Tube Connection, RectuPom

| 2110               | To Fit Tube Size mm |    |    | £            |
|--------------------|---------------------|----|----|--------------|
| <b>21KBK006DPX</b> | 4 x 6               | 17 | 56 | <b>23.35</b> |



Female Thread, BSPP, RectuChem

| 2110               |      |    |    | £            |
|--------------------|------|----|----|--------------|
| <b>21KBIW10FVX</b> | 1/8" | 17 | 53 | <b>37.45</b> |
| <b>21KBIW13FVX</b> | 1/4" | 17 | 53 | <b>37.45</b> |



Quick Fit Tube Connection, RectuChem

| 2110               | To Fit Tube Size mm |    |    | £            |
|--------------------|---------------------|----|----|--------------|
| <b>21KBK006FVX</b> | 4 x 6               | 17 | 56 | <b>42.65</b> |
| <b>21KBK008FVX</b> | 6 x 8               | 17 | 56 | <b>55.15</b> |



Panel Mount, Quick Fit Tube Connection, RectuPom

| 2110               | To Fit Tube Size mm |    |    | £            |
|--------------------|---------------------|----|----|--------------|
| <b>21KBKS06DPX</b> | 4 x 6               | 17 | 68 | <b>26.35</b> |
| <b>21KBKS08DPX</b> | 6 x 8               | 17 | 68 | <b>26.80</b> |

## For Direct Drive & Belt Driven Compressors

see page 1445

Other materials, seals and finishes available on request, please contact our technical department for further details.

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep., Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE