



## Series 23KA



### Page Tech Sheet 511



**Temperature Range:**  
-20°C to +100°C  
Standard Seal NBR



**Maximum Static Working Pressure:**  
PB 35 bar (500 PSI)



Single Shut Off

**Interchangeability:**  
Norgren Dynaquip DC3,  
Hanson 3000, Parker,  
US C4109 1/4",  
Cejn 310, ISO 6150

**Material:**  
Brass Nickel Plated, Buna Seal  
(Standard Series Coupling)

**Application:**  
General Purpose Pneumatic Coupling

**Flow Rate:**  
900 L/Min



Actual Size

Section 3 – Pneumatic QRC

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep, Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives


Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE

### Couplings




Male Thread, BSPT

2310				£
23KAAK13MPN	1/4"	19	60	26.15
23KAAK17MPN	3/8"	19	60	26.35
23KAAK21MPN	1/2"	22	61	27.00



Female Thread, BSPP

2310				£
23KAIW13MPN	1/4"	19	56	26.15
23KAIW17MPN	3/8"	19	55	26.35
23KAIW21MPN	1/2"	24	58	27.00



Hose Tail

2310	To Suit Hose I.D.			£
23KATF06MPN	6mm (1/4")	19	74	26.15
23KATF08MPN	8mm (5/16")	19	74	26.35
23KATF09MPN	9mm	19	74	26.85
23KATF10MPN	10mm (3/8")	19	74	26.85
23KATF13MPN	13mm (1/2")	19	74	27.40

### Plugs



Male Thread, BSPT

2310				£
23SFAK10SXN	1/8"	13	39	6.30
23SFAK13SXN	1/4"	14	42	6.30
23SFAK17SXN	3/8"	17	42	8.40
23SFAK21SXN	1/2"	22	48	12.15



Female Thread, BSPP

2310				£
23SFIW10SXN	1/8"	14	36	6.30
23SFIW13SXN	1/4"	17	36	6.30
23SFIW17SXN	3/8"	19	36	10.05
23SFIW21SXN	1/2"	24	39	13.95



Hose Tail

2310	To Suit Hose I.D.		£
23SFTF06SXN	6mm (1/4")	51	6.30
23SFTF08SXN	8mm (5/16")	51	6.35
23SFTF09SXN	9mm	51	6.95
23SFTF10SXN	10mm (3/8")	51	6.95
23SFTF13SXN	13mm (1/2")	51	7.70

Other materials, seals and finishes available on request, please contact our technical department for further details.