



Series 23KE Self Venting



Page Tech Sheet **512**



Temperature Range:
-20°C to +60°C
Standard Seal NBR



Maximum Static Working Pressure:
PB 8 bar (116 PSI)



Single Shut Off

Interchangeability:

Series 23, ISO 6150,
AFNOR:NF, E19.053,
US-MIL-NORM C 4109

Flow Rate:

900 L/Min

Material:

Brass Nickel Plated, Plug Steel,
Hardened Zinc or Nickel Plated

Application:

General Purpose Pneumatic Coupling,
Self-Venting



Actual Size

Couplings



Male Thread, BSPT

0194



23KEAK13SPN	1/4"	24	65	55.95
23KEAK17SPN	3/8"	25	65	55.95
23KEAK21SPN	1/2"	24	69	55.95



Female Thread, BSPP

0194



23KEIW13SPN	1/4"	24	61	55.95
23KEIW17SPN	3/8"	24	59	55.95



Hose Tail

0194



23KETF06SPN	6mm (1/4")	24	79	55.95
23KETF10SPN	10mm (3/8")	24	79	55.95

Plugs



Male Thread, BSPT

2310



23SFAK10SXN	1/8"	13	39	6.30
23SFAK13SXN	1/4"	14	42	6.30
23SFAK17SXN	3/8"	17	42	8.40
23SFAK21SXN	1/2"	22	48	12.15



Female Thread, BSPP

2310



23SFIW10SXN	1/8"	14	36	6.30
23SFIW13SXN	1/4"	17	36	6.30
23SFIW17SXN	3/8"	19	36	10.05
23SFIW21SXN	1/2"	24	39	13.95



Hose Tail

2310



23SFTF06SXN	6mm (1/4")	51	6.30
23SFTF08SXN	8mm (5/16")	51	6.35
23SFTF09SXN	9mm	51	6.95
23SFTF10SXN	10mm (3/8")	51	6.95
23SFTF13SXN	13mm (1/2")	51	7.70

Other materials, seals and finishes available on request, please contact our technical department for further details.

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep, Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE