



Series 24KA



Page Tech Sheet 513



Temperature Range:
-20°C to +100°C
Standard Seal NBR



Maximum Static Working Pressure:
PB 35 bar (500 PSI)



Single Shut Off



Actual Size

Interchangeability:
Series 23, Cejn 310,
Norgren DC3,
Hanson 3000

Material:
Brass
Application:
General Purpose Pneumatic Coupling

Section 3 – Pneumatic QRC

Hydraulics

Hydraulic QRC

Pneumatic QRC

Ind. Air Prep, Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns & Vacuum

Wash Down & Fuelling

Air Tools

Tools, Hardware & PPE

Couplings



Male Thread, BSPP

0194				£
24KAAW13MPX	1/4"	22	43	12.15
24KAAW17MPX	3/8"	22	43	12.15
24KAAW21MPX	1/2"	22	46	12.15



Female Thread, BSPP

0194				£
24KAIW13MPX	1/4"	22	43	12.15
24KAIW17MPX	3/8"	22	43	12.15
24KAIW21MPX	1/2"	22	46	12.15



Hose Tail

0194	To Suit Hose I.D.			£
24KATF06MPX	6mm (1/4")	21	60	12.15
24KATF08MPX	8mm (5/16")	21	60	12.15
24KATF10MPX	10mm (3/8")	21	60	12.15
24KATF13MPX	13mm (1/2")	21	60	12.70

Plugs



Male Thread, BSPT

2310				£
23SFAK10SXN	1/8"	13	39	6.30
23SFAK13SXN	1/4"	14	42	6.30
23SFAK17SXN	3/8"	17	42	8.40
23SFAK21SXN	1/2"	22	48	12.15



Female Thread, BSPP

2310				£
23SFIW10SXN	1/8"	14	36	6.30
23SFIW13SXN	1/4"	17	36	6.30
23SFIW17SXN	3/8"	19	36	10.05
23SFIW21SXN	1/2"	24	39	13.95



Hose Tail

2310	To Suit Hose I.D.		£
23SFTF06SXN	6mm (1/4")	51	6.30
23SFTF08SXN	8mm (5/16")	51	6.35
23SFTF09SXN	9mm	51	6.95
23SFTF10SXN	10mm (3/8")	51	6.95
23SFTF13SXN	13mm (1/2")	51	7.70

Other materials, seals and finishes available on request, please contact our technical department for further details.